

LIDO-640 WPW

6.5" WATERPROOF 2-WAY PASSIVE WALL-MOUNT SPEAKER PAIR, WHITE

LIDO series is specifically designed for both indoor and outdoor applications in projects with constant voltage or low impedance systems. Thanks to the IP65 protection rating, to the PP woofers, to the UV-resistant PP cabinets, to the stainless-steel metal parts, and to the aluminum grille, these speakers do not fear the rigors of exposure to atmospheric agents.

The high excursion custom transducers guarantee a clear and defined sound, always providing a higher audio quality even at high sound pressures. The power-tap selector allows you to select 3 powers and adapt the speaker to 100V or low impedance systems. The C-bracket allows you to adjust the horizontal (+55°/-55°) and vertical position (+20°/-20°).

LIDO-640 WPW

[9e6bc7e0-cab1-4739-acc4-b893902ff688.jpg](#)

[ec8dfbb9-e9f9-4dfe-b5d6-27434e85113f.jpg](#)

[a9ebe579-ba0c-4ba2-847a-4e6673f6](#)

2-Way Speaker IP65

70V-100V Line Low Impedance

LIDO-640 WPW

6.5" WATERPROOF 2-WAY PASSIVE WALL-MOUNT SPEAKER PAIR, WHITE

HIGHLIGHTS



WEATHER-RESISTANT TRANSDUCERS

Woofer and Dome Tweeter are made of water-resistant materials to allow use in outdoor places exposed to rain and moisture. Material type and thicknesses of the external parts have been designed to maintain a good frequency linearity and dynamic response.

DETAILS DESIGNED FOR A LONG-LIFE CYCLE

All materials are designed to increase speaker life cycle, even when installed in outdoor environments without protections. The cabinet and rubber covers are made of UV-resistant plastic material. The front grille is in aluminum with treatment against atmospheric agents, and the fixing screws are in stainless steel.



LIDO-640 WPW

6.5" WATERPROOF 2-WAY PASSIVE WALL-MOUNT
SPEAKER PAIR, WHITE

PRODUCT DETAILS

KEY FEATURES

2-Way Passive system with 40W RMS Power
IP65 Protection Rating for Outdoor/Indoor Applications
UV-Resistant PP Housing
Built-in 100V Line Transformer
Power Tap Selector for 100V or low-impedance systems
Horizontal and Vertical adjustable C-Bracket
Paintable Housing and Grille

SPECIFICATIONS

Speaker Type	2-Way Passive
IP Rating	IP65
RMS Power (@ 8ohm)	40W
70V Powers	5W – 10W – 20W
100V Powers	20W – 30W – 40W
Frequency Response (-10dB)	65Hz-18kHz
Sensitivity (1w@1m)	92dB
Impedance	8ohm
Woofer	6.5" (165mm), PP cone

Tweeter	0.5" (13mm), Mylar dome
---------	-------------------------

LIDO-640 WPW

6.5" WATERPROOF 2-WAY PASSIVE WALL-MOUNT SPEAKER PAIR, WHITE

Housing	UV-Resistant PP, paintable	
Bracket	C-Bracket with Pan/Tilt adjustable angle and stainless steel screws	
Grille	Perforated aluminum, powder coated paint, acoustic transparent foam inside, paintable	
Color	White	
Product Size (WxDxH)	205 x 182 x 328mm	
Speaker Weight (single unit)	3,475 kg	
Packing Size (WxDxH) (pair)	465 x 245 x 365 mm	
Packing Weight (pair)	8,2 kg	