


ONDA-660TFW

6.5" 2-WAY HI-FI LOW-IMPEDANCE COAXIAL IN-WALL/IN-CEILING SPEAKER

ONDA in-wall speaker series is born to satisfy all those indoor installations where sound pressure and quality higher than normal 70/100V systems are requested.

The ONDA speakers are all low-impedance (8ohm), coaxial, with Kevlar woofers, silk-dome tweeters, precision crossovers; essentially true 2-way speakers for professional applications, but ceiling/wall mount.

The look of the front panel is minimalist and captivating, and reminds recording studio monitor. The frame-less design, with black ABS frame and white magnetic grids, makes the ONDA speakers extremely discreet. Finally, the grids can be repainted to make them even less visible.



2-Way Speaker Low Impedance Frameless Quick Fit System

ONDA-660TFW

6.5" 2-WAY HI-FI LOW-IMPEDANCE COAXIAL IN-WALL/IN-CEILING SPEAKER

PRODUCT DETAILS

KEY FEATURES

2-Way Hi-Fi Coaxial Low-Impedance Loudspeaker

Frame-less Design with Magnetic Grille

Quick-Fit Mounting System with 4 Screws

60W RMS Power

High Excursion Kevlar Woven Cone Woofers

6.5" (165mm) Woofer Diameter

0.76" Silk-Dome Tweeter

Built-In Precision Passive Crossover

+/-2dB High-Frequency Attenuation Selector

SPECIFICATIONS

Speaker Type	2-Way Passive, Coaxial
Frequency Response (-10dB)	60Hz-20kHz
Sensitivity (1W @ 1m)	93dB
RMS Power	60W
Impedance	8 ohm
Woofer	6.5" (165mm), Kevlar Woven Cone
Tweeter	0.76" (20mm), Silk Dome
High-Freq. Attenuator	2-position switch (0dB/-2dB)

ONDA-660TFW

6.5" 2-WAY HI-FI LOW-IMPEDANCE COAXIAL IN-WALL/IN-CEILING SPEAKER

Housing	ABS
IP rate (speaker installed)	IP54
Mounting	Quick mounting system with 4 screws
Grille	Frameless Design, Magnetic Mount, Perforated steel with acoustic transparent foam inside, paintable
Color	Black Housing / White Grille
Cutout Size	Ø 208 mm
Product Size (WxDxH)	Ø 248 x 97 mm
Speaker Weight	1,6 kg
Packing Size (WxDxH)	270 x 270 x 98 mm
Packing Weight	1,9 kg