

EVT-2.60-V55.1


INDOOR LED PANEL FOR COMPOSITE SCREENS FOR RENTAL INSTALLATIONS 2.6MM PITCH 500X500MM

The Event Series is a versatile and high-performance display solution tailored for professional indoor rental applications. Its **2.6mm pixel pitch** ensures exceptional visual clarity, making it ideal for events, exhibitions, and corporate installations where close viewing distances are critical.

Featuring long-lasting, high-quality **Nationstar LEDs**, the panel guarantees consistent brightness, color accuracy, and reliability for demanding environments. The **independent power unit** enhances serviceability, enabling quick and efficient maintenance without interrupting the overall structure.

Engineered for convenience, the panel guarantees **quick installation** and offers layout flexibility, accommodating diverse configurations with ease. **Corner protections** safeguard the LEDs during handling and setup, ensuring durability even in fast-paced rental scenarios.

The **extra-lightweight frame** simplifies transport and assembly, reducing setup time while maintaining structural integrity. The Event Series is the perfect choice for professionals seeking an efficient, robust, and visually stunning display solution.









EVT-2.60-V55.1

INDOOR LED PANEL FOR COMPOSITE SCREENS FOR RENTAL INSTALLATIONS 2.6MM PITCH 500X500MM

PRODUCT DETAILS

KEY FEATURES

LED Module pitch 2.6mm

Suitable for indoor applications

Equipped with long lasting high quality Nationstar LEDs

High refresh rate

Independent power unit for quick and efficient maintenance

Quick installation and layout flexibility

Corner protections

Extra-lightweight frame for easy transport and installation

SPECIFICATIONS

Pixel Pitch	2.6mm
LED Type	Nationstar SMD1515
Module Dimensions (W x H x D)	250 x 250 x 17mm
Module Resolution	96 x 96 pixel
Cabinet Dimensions (W x H x D)	500 x 500 x 78mm
Cabinet Resolution	192 x 192 pixel
Cabinet Weight	7 kg
N. of modules per panel	4
Brightness	800 Nits (average) / 1000 Nits (max)





EVT-2.60-V55.1

INDOOR LED PANEL FOR COMPOSITE SCREENS FOR RENTAL INSTALLATIONS 2.6MM PITCH 500X500MM

Maintenance	Front / Rear
Refresh Rate	? 3840 Hz
Grey Scale	16 Bit
Viewing Angle (H/V)	160°x160°
Operating Voltage	110/240V 50/60 Hz
Operating Temperature	-20° to 60°C
Power Consumption	220W/sqm (Avg), 640W/sqm (Max)
Lifespan	100.000 hours

