

GF82A

ULTRA-COMPACT 8X2" LINE ARRAY COLUMN ACTIVE SPEAKER (BLACK)

GF82A

Active performance in an ultra-compact format

GF82A is an **active column speaker** with **8x2" drivers** and a built-in amplifier, designed with **K-array™ PAT® (Pure Array Technology)**. It delivers **excellent speech intelligibility** and **controlled dispersion**, typical of line arrays, in a sleek and minimal design.

Compact, powerful and ready to go

With **up to 100W RMS output** and **24V DC power supply**, the GF82A is a **versatile and easy-to-integrate solution**, ideal for a wide range of professional installations. The built-in Class-D amplifier and **comprehensive protection circuitry** ensure reliable performance in any application.

Designed for any environment

Thanks to its compact size and **durable ABS enclosure with IP54 rating**, GF82A is ideal for both **indoor and outdoor use** — from hospitality venues and restaurants to public areas, transport hubs, and conference rooms.

Enhanced with dedicated subwoofers

For extended low-frequency response in music applications, GF82A can be paired with the **GS6 subwoofer**, creating a compact and high-performing full-range audio system.

hqE5bOjvOA1L7MH1749472455_GF82T imagine 2 tagliata.png

Class-D

GF82A

ULTRA-COMPACT 8X2" LINE ARRAY COLUMN ACTIVE SPEAKER (BLACK)

HIGHLIGHTS



PURE ARRAY TECHNOLOGY (PAT®)

This technology enables **direct, intelligible and controlled sound**, even in reverberant or complex environments, **without the need for large spaces or bulky loudspeakers**.

ULTRA-COMPACT FORMAT AND IP54 RATING FOR DISCREET INDOOR/OUTDOOR INSTALLATIONS

Just 60 mm wide, with dust and splash protection—perfect for elegant applications in both public and private venues.



GF82A

ULTRA-COMPACT 8X2" LINE ARRAY COLUMN ACTIVE SPEAKER (BLACK)

PRODUCT DETAILS

KEY FEATURES

100W RMS Class D Integrated Amplifier: Reduces the need for external amplifiers, simplifying installation and optimizing costs for the integrator.

Ultra compact and discreet design (60x600x65 mm, only 1.6 kg): perfect for installations where space is limited or aesthetics are fundamental (hotels, restaurants, meeting rooms).

SPECIFICATIONS

Type	Active loudspeaker
Transducers	8x2" ferrite magnet woofer
Frequency Response	150 Hz - 20 kHz (-6dB)
Max SPL	105 dB
Rated Power	200 W
Coverage	V. 15° H. 90°
Connectors	2x Phoenix connector (4-pin euroblock) Balanced Line in Mute contact Power out 24V DC IN (power supply not included)
Mains Connector	4PIN Euroblock, 2x Phoenix 1,5/ 4-ST-3,81 compatible
Nominal Impedance	16 ?
Amp Module	1-channel Class-D audio amplifier
Output Power	100W @ 2? (24V power)
Power Consumption	30W Rated Load 1/8 Max Power

GF82A

ULTRA-COMPACT 8X2" LINE ARRAY COLUMN ACTIVE SPEAKER (BLACK)

Protections	Thermal Protections (Power limiting - Thermal Shutdown), Short-circuit/overload output protections	
Operating Range	12-24 V DC	
Dimensions (W x H x D)	60x600x65 mm (2.36x23.62x2.56 in)	
Weight	1,6 kg (3.53 lbs)	
Material	ABS	
Colors	Black	
IP Rating	IP54	