

AC48II

4 INPUT – 8 OUTPUT DIGITAL AUDIO PROCESSOR

4 Input – 8 Output Digital Audio Processor

AC48II

[d7557550-aeca-4423-9386-ff78796267ea.jpg](#)

AC48II

4 INPUT – 8 OUTPUT DIGITAL AUDIO PROCESSOR

PRODUCT DETAILS

KEY FEATURES

48kHz Sampling Rate, 40-bit DSP Processor, 24-bit AD/DA Converter

Input Processing Includes Gain, Mute, Link, High-Cut, Low -Cut, Noise Gate, 5PEQ, Phase, Delay

Output processing includes Crossover, 6PEQ, Gain, Mute, Compressor/Limiter, Phase, Delay, Link

Matrix with Free Assignment for every Input and Output

Peak, H-shelf, L-shelf, LP-6dB, LP-12dB, HP-6dB, HP-12dB filter styles with adjustable PEQ frequency, Gain (with 0.1dB steps) and Bandwidth

Butterworth, Linkwitz- Riley, Bessel High-cut and Low-cut filters with slope from -6dB/oct to -48dB/oct

Compressor/Limiter with adjustable Threshold, Soft Knee, Ratio, Attack and Release time

Noise gate with adjustable Threshold, Hold time, Attack and Release time

Linkable and Revisable Input and Output Channel Parameters

680ms Delay Time (0.021ms steps) for each Input and Output

Parameter setting of each channel can copy freely

Built-in Signal Generator

5-Segment High-Precision Level Indicators and Key Indicators on front panel for all Inputs and Outputs

Security protection function

30 User Presets, 1 Factory Preset, Device Parameters and Single Preset File can be stored and recalled inside de Device, or they can be saved in and recalled from a Computer through the PC Software

USB and RS-232 Controlling Ports, Online remote control and 255 units linkable through RS-485

SPECIFICATIONS

AC48II

4 INPUT – 8 OUTPUT DIGITAL AUDIO PROCESSOR

Digital Processing	24-bit Sigma/Delta Converters - 48kHz Sampling Rates
Frequency Response	20Hz-20kHz, -0.3dBu
S/N Ratio	>110dBu
Distortion (THD)	<0. 01 @ 1kHz (0dBu)
Cross-talk	<100dB below full scale
Input Type	Balanced XLR
Max. Input Level	+15dBu
Impedance	1M Ω Stereo; 500k Ω Mono
Output Type	Balanced XLR
Max. Output Level (bypass)	+15dBu
Impedance	<500 Ω
Display	20 x 2 LCD Display for Parameters Setting and Function Select
Power Supply	AC~95V-264V – Fuse
Dimension (LxWxH)	82x205x44CM
Weight	2.88kg