GH12


12" PASSIVE COAXIAL LOUDSPEAKER WITH CONTROLLED DIRECTIVITY AND STAINLESS STEEL ENCLOSURE


GH12 is a high-efficiency passive coaxial loudspeaker, engineered to deliver powerful and accurate sound in a compact, weather-resistant format. Equipped with a 12" woofer and 1" compression driver, it features a slim array design with cardioid dispersion, minimizing unwanted sound spill and ensuring even coverage across the listening area.


Its stainless steel cabinet and IP54 rating make GH12 perfect for demanding indoor and outdoor applications, including live events, auditoriums, transportation hubs, stadiums, theme parks, and large clubs. Multiple units can be combined to form a line array for extended coverage.

Designed to work seamlessly with K-array amplifiers such as the GA43 and GA46, GH12 ensures optimal power handling and precise control. It’s a reliable, high-performance solution for sound engineers, musicians, and AV professionals seeking compactness, durability, and clarity.

GH12


82f6e457-58fc-4bad-a65c-38009d3df244.png


c019388c-e09e-49c0-8f79-9f8a8cf990da.png


c517607f-e56f-4454-a68f-efa4dad5


Coaxial Speaker 2-Way Speaker

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

GH12

12" PASSIVE COAXIAL LOUDSPEAKER WITH CONTROLLED DIRECTIVITY AND STAINLESS STEEL ENCLOSURE

HIGHLIGHTS




COMPACT AND PORTABLE DESIGN

The GH line's compact and portable design makes it easy to transport and set up for any event or installation.
Whether you need to cover a small room or a large stadium, the GH speakers are designed to provide even sound coverage and control.

STAINLESS STEEL ENCLOSURE WITH IP54 RATING FOR PROFESSIONAL OUTDOOR/INDOOR USE

Durable and weather-resistant design, perfect for live events and permanent installations in challenging environments.



Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

GH12

12" PASSIVE COAXIAL LOUDSPEAKER WITH CONTROLLED DIRECTIVITY AND STAINLESS STEEL ENCLOSURE

PRODUCT DETAILS

KEY FEATURES

- Designed for high performance applications
- High efficiency in a compact box
- Weather resistant

SPECIFICATIONS

Type	Passive loudspeaker
Transducers	12” coaxial woofer with 1” compression driver
Continuous Power	200W
Peak Power	400W
Impedance	32?
Frequency range	125hz – 20khz (-6db average)
Maximum SPL	129dB (peak)
Coverage	V.30° - H.90°
Connectors	SpeakOn NL4 1+ 1- (signal); 2+ 2- (through)
Dimensions (WxHxD)	327mm x 334mm x 198mm
Weight	13.8Kg
Material	stainless steel
Color	Black
IP Rating	IP54

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it