

27X10W RGBW 4IN1 LED PAR WITH 25° BEAM FOR INDOOR USE

The Centolight **Scenic 2710** PAR Light is a versatile high-performance lighting fixture tailored for dynamic and creative lighting applications. Featuring 27 x 10W 4-in-1 RGBW LEDs, it delivers bright and vibrant colors with a beam angle of 25°, making it ideal for stage performances, events, and architectural lighting. With a light source lifespan of up to 50,000 hours, the Scenic 2710 ensures reliable, long-term operation.

The fixture offers a wide range of operation modes, including DMX512, Auto, Master/Slave, and Sound, providing flexibility for both standalone and integrated setups. Control is made simple with two DMX channel modes (8CH A and 8CH B), allowing precise adjustments for color mixing, effects, and performance synchronization.

Advanced features include a strobe effect with a speed range of up to 20Hz and a smooth linear dimmer for seamless transitions. These capabilities enable remarkable effects, from subtle fades to high-energy flashes, enhancing the visual impact of any production.

Designed for user convenience and professional performance, the **Scenic 2710** combines durability with creative control, making it an essential tool for lighting designers, event planners, and entertainment professionals.









27X10W RGBW 4IN1 LED PAR WITH 25° BEAM FOR INDOOR USE











27X10W RGBW 4IN1 LED PAR WITH 25° BEAM FOR INDOOR USE

PRODUCT DETAILS

KEY FEATURES

Ideal for stage performances, events, and architectural lighting

Light Source: 27 x 10W RGBW 4in1 LEDs

Beam Angle: 25°

2 DMX Channel modes (8CH A and 8CH B)

Electronic strobe with adjustable speed

Smooth dimming function

Dynamic color transitions for mood and atmosphere in any setting

Auto, Master/Slave, DMX512 and Sound Control modes

Durable, heat-resistant lens

Fin+Fan heat dissipation cooling system

SPECIFICATIONS

Light Source	27x10W 4-in-1 RGBW LEDs
Light Source	Lifespan 50.000 hours
Beam Angle	25°
Antistatic	Up to 2000V HBM
Lens material	High temperature resistant PC+PMMA
Body material and coating	Aluminum alloy, fine-sand paint
Cooling System	Fin+Fan heat dissipation





27X10W RGBW 4IN1 LED PAR WITH 25° BEAM FOR INDOOR USE

Control Mode	DMX, Master/Slave, Auto, Sound
DMX Channels	8CH A /8CH B Modes
DMX Connectors	3-pin XLR Input/Output
Power Connectors	Powercon Input/Output
IP Grade	IP20
Input Voltage	AC100V-240V (50/60Hz)
Power Consumption	200W
Ambient Temperature	0° - 35°C
Fixture Dimensions with brackets installed (WxDz	274 x 281 x 216 mm(10.78 x 11.06 x 8.50 in.)
Packing Dimensions (WxDxH)	265 x 265 x 340 mm(10.43 x 10.43 x 13.38 in.)
Product Weight	2.8 kg – 6.17 lbs.
Package Weight	3.6 kg - 7.94 lbs.