

GS218


HIGH PERFORMANCE 2X 18" PASSIVE SUBWOOFER

GS218 is a passive subwoofer equipped with two high-performance 18" drivers, designed to deliver deep and powerful bass for a wide range of indoor and outdoor applications. Its birch plywood cabinet with weather-resistant treatment ensures reliability and durability even in the most demanding environments, making it ideal for touring events, stadiums, theme parks, auditoriums, clubs, and permanent installations.

Thanks to its rugged design and premium components, the GS218 achieves high-level performance, with an extended frequency response down to 30 Hz and a maximum SPL of 138 dB, delivering deep and controlled sound even in large-scale settings.

GS218 is the perfect low-frequency complement to KGEAR loudspeakers such as the GH412 or GH12, enabling the creation of high-power, high-definition audio systems. Compatible with KGEAR GA43 and GA46 amplifiers, it ensures optimal power management and precise control.

Reliable, powerful, and versatile, GS218 is the go-to choice for professional audio rental companies, installers, and consultants for medium-to-large-scale applications where top performance and system compatibility are essential.



GS218

HIGH PERFORMANCE 2X 18" PASSIVE SUBWOOFER

HIGHLIGHTS



PROFESSIONAL PERFORMANCE IN HIGH-DEMAND CONTEXTS

The GS18 is **the ideal choice for professionals** working in **large venues and harsh environmental conditions**, combining **extreme power (132 dB SPL)**, **durability** and **flexible integration**.

GS218

HIGH PERFORMANCE 2X 18" PASSIVE SUBWOOFER

PRODUCT DETAILS

KEY FEATURES

High power rating: with its 3000 W at 4 Ω it guarantees a powerful and stable output, suitable for large venues, live events and professional PA systems.

Powerful 18" woofer with ferrite magnet: offers an extended frequency response up to 30 Hz and a maximum sound pressure of 138 dB, for deep and controlled bass even in large rooms.

Cabinet in birch plywood with IP43 protection: resistant to atmospheric agents and impacts, it is perfect for indoor and outdoor installations in professional contexts.

SPECIFICATIONS

Type	Passive subwoofer
Transducers	2x 18" ferrite magnet woofer
Frequency Response	30 Hz - 150 Hz (-6 dB)
Max SPL	138 dB
Rated Power	3000 W
Connectors	2x SpeakON NL4
Nominal Impedance	4 Ω
Dimensions (W x H x D)	1035x614x600 mm (40.75x24.17x23.6 in)
Weight	58 kg (127,86 lbs)
Material	Birch Plywood
Colors	Black
IP Rating	IP43

GS218

HIGH PERFORMANCE 2X 18" PASSIVE SUBWOOFER

Coverage

Omni