

HYPER-PRO 10 PLUS

10" 2-WAY ACTIVE LOUDSPEAKER WITH DSP

HYPER-PRO 10 PLUS

The new Hyper-Pro Plus speakers represent a new important stage in the evolution of the famous **Hyper series** by Soundsation. The power, audio quality and convenience of the previous models are now integrated with the functions which are essential for those who professionally use a speaker as a work tool.

600W continuous **D-Class** amplifier (700W for 12" and 15" models), selected woofers and compression drivers, **DSP** for Crossover control, EQ, **2-Band Limiter**, **phase alignment** and **delay optimization** of woofers and compression drivers. All this technology can ensure high performance and maximum audio quality in any use conditions.

The control panel includes two XLR-Combo Mic/Line inputs, the Mix output and **4 Audio Programs** (Music, Live, Monitor, Vocal) to quickly adapt the speaker to the main uses.

The stylish and sturdy cabinet is designed to be installed vertically on the floor or on a 35mm pole/tripod, and also suspended horizontally or vertically thanks to the 4 M8 fixing points.

2964b76f-20f2-4bf2-90be-5e8bd15bffd

ed92b2dc-b55d-4625-abc2-fbf9dcf83b44

c00e8d37-4a2c-40ac-8353-2d0ec9060

2-Way Speaker Class-D DSP

HYPER-PRO 10 PLUS

10" 2-WAY ACTIVE LOUDSPEAKER WITH DSP

PRODUCT DETAILS

KEY FEATURES

2-way Loudspeaker, Bass-Reflex Design

600W Continuous / 1200W Peak Class-D amplifier

90°H x 60°V Coverage

DSP for Crossover, EQ and 2-Band Limiter Control, Phase and Time Optimization

4 EQ Presets (Music, Live, Monitor, Speech)

2 Mic-Line Combo Inputs and Balanced Mix Output

On-off key for the Front LED

35mm Adapter for Pole or Tripod Stand

4 Fixing Points for M8 Eyebolts

SPECIFICATIONS

System Type	2-Way Active 10" Loudspeaker, Bass-Reflex
-------------	---

Power Rating	600W Continuous, 1200W Peak
--------------	-----------------------------

Frequency Response	60Hz-20kHz
--------------------	------------

Max SPL	128dB SPL
---------	-----------

LF Driver	10" Custom Woofer
-----------	-------------------

HF Driver	1" Compression Driver
-----------	-----------------------

Coverage	90°H x 60°V
----------	-------------

Crossover Frequency	2.8kHz
---------------------	--------

Input Connectors	2x Balanced Combo XLR/1/4" Jack Connectors
------------------	--

Output Connectors	1x Balanced XLR Mix Output
-------------------	----------------------------

HYPER-PRO 10 PLUS

10" 2-WAY ACTIVE LOUDSPEAKER WITH DSP

Indicators	Power, Clip, Preset, Front Led	
EQ	4 Presets (Music, Live, Monitor, Vocal)	
DSP	Crossover, EQ, Dual Band Limiters, Phase and LF/HF Time Alignment	
Controls	2x Channel Gain, Master Volume, Front Led On/Off, Ground Lift, EQ Preset	
AC Power	100-120V~ or 220-240V~ 50/60Hz (User Selectable)	
Power Consumption	315W Typical	
Cabinet	Polypropylene	
Handles	1 on Sides, 1 on Top	
Monitor Angle	45°	
Finish	Black	
Grille	Powder-Coated Steel with Acoustic Foam	
Pole-Mount	36mm Pole Socket	
Flying Points	4x M8	
Unit Size (WxDxH)	302 x 310 x 529 mm	
Net Weight		11 Kg
Carton Size (WxDxH)		370 x 360 x 571 mm
Packed Weight		12.8Kg