

SCWF5

WATERPROOF DMX CONNECTOR (XLR 5P F)

SEETRONIC waterproof DMX connector (XLR 5P Female).

SCWF5

SCWF5

WATERPROOF DMX CONNECTOR (XLR 5P F)

PRODUCT DETAILS

KEY FEATURES

Waterproof XLR connector range for outdoor waterproof class IP65

Strong zinc die-casting shell, long life and high reliability

Metal housing with inner thread increase retention force and makes assembly easier and faster

Colored boots available for coding or identification

Boot with polyurethane gland gives high protection to cable bending stresses

SPECIFICATIONS

Capacitance between contacts	7pF
Contact resistance	3m
Dielectric strength	1.5kVdc
Insulation resistance	>10G (initial)
Rated current per contact	7.5A
Rated voltage	<50V
Insertion force	20N
Withdrawal force	20N
Service life	1000 mating cycles
Wiresize	Max.1.0 mm ²
Wiresize	Max.18 AWG
Locking device	Latch lock
Boot	Polyurethan
Contacts	Cu alloy

SCWF5

WATERPROOF DMX CONNECTOR (XLR 5P F)

Contact plating	Au
Insert	Polyamide (PA66+30%GF)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Cr
Strain relief	Polyacetal (POM)
Flame-retardant grade	UL94HB
Protection class	IP65
Temperature range	-30?to+80?