

MOOD L60 SPOT

SOUNDSATION LED SPOT MOVING HEAD 60 W MOOD L60 SPOT

MOOD L60 SPOT is part of a wider range of SOUNDSATION intelligent LED moving head lights. This lighting is compact, lightweight and very easy to use. It has been designed to meet the demands of more customers. Thanks to the 60W high-brightness white LED, with a lifetime of about 50,000 hours, it is extremely bright and reliable, the 20° beam angle, and the gobos wheel with 7 colours. And a lightweight and high-performance spot product to suit various lighting applications. Not only that, but thanks to its 16-bit precision in driving and motion control, it creates strobe effects, precise dimmers and extremely refined positioning. Finally, the multifunctional LED display has been developed to help the user configure the unit, making it easy to use, reliable in performance and versatile in application. A MUST for all lighting professionals.

MOOD L60 SPOT

[f18ea6c0-214e-464d-9065-708943a956d2.jpg](#)

[58d564ae-d78c-4c65-b9db-a35183b98533.jpg](#)

[46aefd04-2c88-4c7d-9266-20dd4](#)

DMX-512 Control Fan Controlled by Processor

MOOD L60 SPOT

SOUNDSATION LED SPOT MOVING HEAD 60 W MOOD L60 SPOT

PRODUCT DETAILS

KEY FEATURES

60W high-brightness white LED with a service life of approximately 50,000 hours

Beam angle of 20°

0-100% Electronic dimmer

0-20Hz Strobe effect

7-colour colour wheel

Gobo wheel with 7 gobos

SPECIFICATIONS

LED	60W high-brightness white, with a service life of approximately 50,000 hours	
Beam angle	20°	
Electronic dimmer	0-100%	
Strobe effect	0-20Hz	
Colour Wheel	7 colours + White, Rainbow effect and Colour Rotation	
Gobo wheel	7 gobos + White, Gobo shake Gobo rotation	
Pan/Tilt	540° / 270°	
Controls	9CH/11CH DMX512, Master/slave, Auto, Sound	
Voltage	AC100V-240V - 50/60Hz	
Power rating	90W	
Power socket	IEC Europlug	

MOOD L60 SPOT

SOUNDSATION LED SPOT MOVING HEAD 60 W MOOD L60 SPOT

DMX In-out connector	3 pin XLR
Operating temperature	0-40°C
Unit weight	2.9 kg
Unit dimensions (WxDxH)	158 x 145 x 280 mm
Packaging weight	3.3 kg
Packaging dimensions (WxDxH)	230 x 200 x 290 mm