

TriMotion

THREE-WAY DESIGN LOUDSPEAKER WITH 15", 8" AND 1.5" DRIVERS (CUSTOM COLORS AVAILABLE UPON REQUEST)

The Tri Motion is more than a loudspeaker—it's a statement of style and sonic excellence. Designed for premium spaces such as high-end clubs, designer restaurants, and VIP lounges, the Tri Motion stands out with its controlled, high-impact performance and visually captivating triangular form.

Its three-way configuration—featuring a 15" woofer, 8" midrange and 1.5" HF compression driver—delivers crystal-clear reproduction across the spectrum. Triangular waveguides enhance directivity control (90°H x 60°V), ensuring precise sound coverage and improved audience focus.


Thanks to its internal electronic HF protection, the Tri Motion maintains consistent reliability even at high outputs. Its low-resonance fibreglass composite enclosure ensures clean sonic output, while the integrated mounting system offers both flown and floor-mounted options.

With custom colour options available, it effortlessly blends into any high-design environment—serving as both a sonic centerpiece and a visual signature.



TriMotion

THREE-WAY DESIGN LOUDSPEAKER WITH 15", 8" AND 1.5" DRIVERS (CUSTOM COLORS AVAILABLE UPON REQUEST)



TriMotion

THREE-WAY DESIGN LOUDSPEAKER WITH 15", 8" AND 1.5" DRIVERS (CUSTOM COLORS AVAILABLE UPON REQUEST)

HIGHLIGHTS



LOW-RESONANCE FIBREGLASS COMPOSITE CONSTRUCTION

The use of **fibreglass material** ensures a **rigid and stable enclosure**, minimizing cabinet resonance and contributing to **clearer and more accurate audio reproduction**.

THREE-WAY CONFIGURATION WITH 15", 8" AND 1.5" DRIVERS

The combination of a 15" woofer, an 8" midrange and a 1.5" compression driver enables **extremely detailed and dynamic reproduction** throughout the entire frequency range. This configuration ensures a coherent and balanced response with deep bass, natural midrange and precise high frequencies, making it ideal for applications where **definition and sonic clarity are paramount**.



TriMotion

THREE-WAY DESIGN LOUDSPEAKER WITH 15", 8" AND 1.5" DRIVERS (CUSTOM COLORS AVAILABLE UPON REQUEST)

TRIANGULAR WAVEGUIDES



Designed for direct dispersion control, the triangular profile waveguides **ensure an even and predictable acoustic distribution** with a 90° horizontal and 60° vertical pattern. This geometry **reduces unwanted reflections** and concentrates acoustic energy on the audience, being particularly effective in difficult or high-density environments.

CUSTOM COLORS AVAILABLE UPON REQUEST

In addition to the 3 iconic Void brand colors -red, white and black- TriMotion can be produced in several other custom colors (the colors visible in the image are examples for illustrative purposes)



TriMotion

THREE-WAY DESIGN LOUDSPEAKER WITH 15", 8" AND 1.5" DRIVERS (CUSTOM COLORS AVAILABLE UPON REQUEST)

PRODUCT DETAILS

KEY FEATURES

Built-in electronic protection on high frequency: ensures reliability and operational safety even during prolonged use at high levels.

High sound pressure (up to 141 dB peak): capable of handling large volumes accurately and without distortion, suitable for high-impact settings.

Integrated suspension and mounting system: designed for versatile installations, it allows both suspended and floor-mounted use with appropriate accessories.

SPECIFICATIONS

Frequency Response	120 Hz - 20 kHz ±3 dB
Efficiency	LF 107 dB 1W/1m HMF 110 dB 1W/1m
Crossover Points	LF 120 Hz and 500 Hz HMF 500 Hz - Passive 1.4 kHz
Nominal Impedance	LF 8 ? HMF 8 ?
Power Handling	LF 700 W AES MHF 250 W AES
Maximum Output	135 dB cont, 141 dB peak
Driver Configuration	1x 15" LF 1x 8" MF 1x 1.5" HF compression driver
Dispersion	90°H x 60°V
Protection	Internal Electronic Control
Connectors	2x 4-pole speakON NL4
Weight	47.1 kg (103.8 lbs)
Enclosure	Fibreglass composite
Rigging	Integral mounting system

TriMotion

THREE-WAY DESIGN LOUDSPEAKER WITH 15", 8" AND 1.5" DRIVERS (CUSTOM COLORS AVAILABLE UPON REQUEST)

Colors

Available in the three Void standard colors Red, Black and White (custom colours available upon request)

Dimensions (W x H x D)

818.73mm x 467.75mm x 728.04mm