

VOXTAKER 192 PRO

PREMIUM QUALITY 192KHZ/24BIT USB STUDIO MICROPHONE KIT

VoxTaker 192 PRO is a groundbreaking technology studio microphone for professional recording. It combines dual high-precision large diaphragm condenser capsule, precision FET pre-amplification circuitry, real 24Bit/192kHz sampling accuracy, and USB 2.0 high-speed audio processing chip. It is compatible with all recording software and ASIO audio drivers and offers a professional driver interface with the newest 2.0 class audio device definition. The built-in monitor interface with 3.5mm stereo headphone jack, volume and Gain controls, provides real-time zero latency monitoring for maximum comfort during recording. The transducing element is a dual-condenser golden-plated large diaphragm capsule with selection of Uni/Bi/Omni-directional polar pattern. All these features make the VoxTaker 192 PRO the perfect tool for any capturing need: from human voice to acoustic instrument miking, to background music and choral recording. It is a real helper for music creation.

VOXTAKER 192 PRO

[39f9ed1f-920c-4190-a857-6c7a7354ba2c.jpg](#)

[b5708996-177d-416f-a490-e9cb3cea63c4.jpg](#)

[26c71ada-1703-485a-a321-3b0014](#)

[2a4a537d-90b4-4819-a171-115f9ad12bba.jpg](#)

[94f0a7ce-1394-4bc5-b0fb-98939ca69fb4.jpg](#)

[7372ac14-3597-431e-be58-72e1ffd](#)

VOXTAKER 192 PRO

PREMIUM QUALITY 192KHZ/24BIT USB STUDIO MICROPHONE KIT

PRODUCT DETAILS

KEY FEATURES

- Professional 34mm Pressure Gradient Transducer
- Selectable Uni/Dual/Omni Directional Polar Patterns
- High Quality FET Preamp
- Strong Output Signal without Distortion
- High-speed AD/DA conversion technology
- Up to 192kHz Sample Frequency (192kHz can only be used under USB 2.0 fast mode)
- Up to 24bit Resolution
- USB 2.0 high-speed and full-speed modes compatible
- Zero latency monitoring and Hi-Fi recording
- Maximum compatibility with Windows and Mac OS computers
- Compatible with variety of recording applications and ASIO audio driver
- Low Power Consumption
- High Absorption Shock-mount
- Stylish and Innovative Pop Filter
- Aluminum Case

SPECIFICATIONS

Element	34mm Pressure Gradient Condenser Transducer
Polar Pattern	Uni/Dual/Omni Directional, selectable

VOXTAKER 192 PRO

PREMIUM QUALITY 192KHZ/24BIT USB STUDIO MICROPHONE KIT

Frequency Response	20Hz~20KHz
Sensitivity	-34dB $\pm$ 2dB (0dB=1V/Pa @ 1kHz)
Max. Input SPL	132dB (@ 1kHz =1% T.H.D)
Output Impedance	150 ohm $\pm$ 30% (@ 1kHz)
Load Impedance	=1000 ohm
Self-Noise	16dB A-weighted
S/N Ratio	78dB
Power Requirement	USB Power
Microphone Size (WxHxD)	188x50x50 mm
Microphone Weight	252 g
24 Bit AD/DA fast conversion	
USB 2.0 high speed audio processing chip	
16/24Bit sampling resolution, with 44.1k/48k/96k/192kHz (192kHz can only be used under USB2.0 fast mode)	
Embed USB2.0 transceiver (bandwidth is up to 480MB)	