SCENIC 2710WP

27X10W RGBW 4IN1 LED PAR LIGHT FOR OUTDOOR USE (IP65)

SCENIC 2710WP

The Centolight **Scenic 2710WP** waterproof PAR Light is a powerful and adaptable lighting fixture engineered for professional indoor and outdoor environments. Equipped with 27 x 10W RGBW 4-in-1 LEDs, it delivers intense and vibrant illumination with a 25° beam angle, perfect for enhancing stage performances, architectural displays, and outdoor events. Built to endure challenging conditions, its IP66-rated housing ensures reliable operation in rain, dust, and other harsh weather scenarios, making it ideal for both temporary setups and permanent installations.This versatile light offers multiple operating modes, including DMX, Auto, and Master/Slave, to suit a variety of creative and technical needs. With support for DMX512 and RDM protocols, it features 9-channel and 6-channel DMX modes, enabling precise control over color mixing, color transitions, and effects.Designed for both creativity and durability, the **Scenic 2710WP** combines professional-grade features with long-term performance. Whether used for live shows, architectural lighting, or outdoor events, this fixture offers exceptional reliability and flexibility for lighting professionals.

55478a25-aebb-40e1-b4d8-cb1ab2ffaf9e.jpg

5067b595-3999-49d0-9789-0894e1130f8a.jpg

3355a3eb-cfed-4673-854b-e45dd3a

DMX-512 Control

RGBW 4in1 LED Technology

RDM Communication

IP65

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

SCENIC 2710WP

27X10W RGBW 4IN1 LED PAR LIGHT FOR OUTDOOR USE (IP65)

PRODUCT DETAILS

KEY FEATURES

- Made to resist the rigors of external weather conditions
- Suitable for both outdoor and indoor live and architectural applications
- IP66 protection degree with waterproof connectors
- DMX512 and RMD protocols, Master/Slave and Auto-run modes
- Light source 27x10W 4-in-1 RGBW LEDs
- 2 DMX Channel modes (6CH and 9CH)
- Electronic strobe with adjustable speed
- Smooth dimming function
- Dynamic color transitions for mood and atmosphere in any setting

SPECIFICATIONS

Light Source	27x10W 4-in-1 RGBW LEDs
Light Source	Lifespan 50.000 hours
Beam Angle	25°
Antistatic	2000V HBM
Lens material	High temperature resistant PC+PMMA
Body material and coating	Aluminum alloy, fine-sand paint
Control Mode	DMX, Master/Slave, Auto
DMX Channels	6CH, 9CH

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

SCENIC 2710WP

27X10W RGBW 4IN1 LED PAR LIGHT FOR OUTDOOR USE (IP65)

DMX Connectors	Waterproof 3-pin XLR Input/Output
Power Connectors	Waterproof Truecon Input/Output
Display	TFT LCD
IP Grade	IP66
Input Voltage	AC100V-240V (50/60Hz)
Power Consumption	200W
Ambient Temperature	0° - 35°
Fixture Dimensions with brackets installed (WxDxH)	304 x 318 x 238 mm(11.97 x 12.52 x 9.37 in.)
Packing Dimensions (WxDxH)	300 x 300 x 360 mm(11.8 x 11.8 x 14.17 in.)
Product Weight	5.9 kg – 13 lbs.
Package Weight	6.7 kg – 14.8 lbs.

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it