

CM-S56T-K

6" SURFACE MOUNT LOUDSPEAKER (COUPLE)

Drawing on our club loudspeaker manufacturing heritage, the versatile two-way CM-S54T, CM-S56T and CM-S58T produce premium-quality audio. Available in black or white, these new units are perfect for discreet installation in a variety of spaces where reliability is crucial, and the loudspeakers can even be used for some applications outdoors.

These affordable and adaptable new arrivals in the CM Series include a host of features including transformer taps – ideal if you need a professional and adaptable fixed installation solution.

CM-S56T-K

9e0600e6-d6a0-403a-95a9-7168810f41eb.png

27a83649-8c00-42fb-9667-fa32125b1ca2.png

1015602c-88d5-467e-95cc-8655

CM-S56T-K

6" SURFACE MOUNT LOUDSPEAKER (COUPLE)

PRODUCT DETAILS

KEY FEATURES

Soft dome tweeter

Newly developed Vortex Bass Accelerator

Flexible 8 ohms impedance

Dust and water resistant

U bracket

Original curved enclosure design

Color: Black

SPECIFICATIONS

Two-way passive, reflex-loaded

Frequency response (- 10 dB, Typical) 80 Hz - 20 kHz

Sensitivity (1W/1m) 88 dB

Nominal Impedance 8 ?

Power Handling (RMS/Program) 60 W / 120 W * IEC60268-5

Transformer taps 70 V 60 W / 30 W / 15 W / 7.5 W

Transformer taps 100 V 60 W / 30 W / 15 W

Dispersion 110 °H × 110 °V

Maximum SPL 113 dB (peak) * Calculated from the power handling and sensitivity

LF 6" (152 mm) cone

HF 1" (25 mm) silk dome tweeter

Connectors Euroblock (4 pin) × 1 (input +/-, loop-thru

CM-S56T-K

6" SURFACE MOUNT LOUDSPEAKER (COUPLE)

Rigging and Hardware

1 × U-bracket 2 × M6 threaded mounting points on rear

Grille

Punched Aluminum

Enclosure PP

Dimensions (WxHxD) 214.1 x 332.3 x 183.5 mm

Weight

5.1 kgs

Environmental IP54