2313000000

FENDER® LINK I/O™, US, CA, EU, AU, JP

The perfect tool to capture your next riff, the Fender Link I/O™ is a studio-grade audio interface that can fit in your pocket. The Fender Link I/O provides pristine, bi-directional audio over USB connection, making it a one stop shop for connecting your instrument and headphones to your phone, tablet, Mac, or PC.

Featuring an input stage designed to replicate the dynamic response of Fender's world-famous amplifiers and uncompromising 24-bit / 96kHz audio, the Fender Link I/O delivers high fidelity tone from any passive or active instrument straight into your device. The integrated input meter and mix control provide the ultimate latency-free monitoring experience, while the weighted body ensures a stable workflow in any environment.

Whether you're tracking your next big song or practicing through your favorite amp simulator app, take Fender® quality recording on the go with the Fender Link I/O.

2313000000

8d1aa7ca-a7a8-4f16-9590-f4e078434f76.png

05a54ff0-da41-4538-972e-2ea49df4eba4.png

cf067c52-6763-4214-86bd-3fcedf21

9a22f90f-1768-459e-85e6-641507c1629f.png

d37501de-f44e-4efb-96aa-99678017d59b.png

7e3825ac-391a-4d9d-a767-1ae31

966661f1-9c8b-4132-8872-61487daafdec.png

391e99c0-1438-4747-96c7-c43e291f2581.png

51a5196b-9ecb-4e65-a856-fb36f9

953a578a-9c70-41fb-8add-8e74b7124550.png

9cbbdd82-9825-41f7-94e7-687d3ee4f752.png

1bd862a5-c831-412f-a6b6-57d2d

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

2313000000

FENDER® LINK I/O™, US, CA, EU, AU, JP

PRODUCT DETAILS

KEY FEATURES

- Studio quality 24-bit / 96kHz analog to digital conversion for high fidelity tone
- High impedance input stage reacts just like an amplifier input jack
- Side mounted mix control for monitoring with lowest possible latency
- Side mounted pad switch accommodates high output and active instruments
- Monitor your recording level in real time with the reactive LED signal meter
- Weighted body with anti-skid silicone feet for stable recording on any surface
- Powered by the USB-C® connection, no power adapter needed
- Wide compatability across iOS, Andriod, Mac, and PC devices

SPECIFICATIONS

Inputs	One - 1/4"
Headphone	Jack1/8" Stereo
Voltage	USB Bus Powered
Digital Audio Bit Depth	24-bit
Instrument Input Connection Type	1/4"
Headphone Outputs Connection Type	
Audio Controls	
Supported Sample Rates	44.1k, 48k, 88.2k, 96kHz
Included Accessories	USB-C to USB-C Cable
Dimensions	2.20x6.30x7.00 IN / 38.1x25x8 mm

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it