MFN300

MULTIFUNCTION CARD

The Novastar MFN300 Multifunction card combines a wide range of functions in just one device.

The card offers connection options for light and temperature sensors, an RS232 connection, a 3.5mm audio output and eight integrated relay contacts. The device can be looped into the signal chain at any point.

241fcee6-a424-4b48-bcd1-1c6d4d9495b8.jpg

MFN300

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

MFN300

MULTIFUNCTION CARD

PRODUCT DETAILS

KEY FEATURES

- 1x RS-232 Serial port
- 2x Gigabit Ethernet ports for connection before the first receiving card, between any two receiving cards, or after the last receiving card
- Timer function, able to replace a timer and delayer
- 4x Sensor ports to connect temperature sensors, or light sensor for automatic brightness adjustment
- 8x Power switch control relay contacts
- 1x TRS balanced 3.5mm audio output

SPECIFICATIONS

Input Voltage	DC 3.3V to 5.5V
Rated Current	0.38 A
Maximum Power Consumption	2.5W
Working Temperature	from -20°C to +75°C
Storage Humidity	0% RH to 90% RH, non condensing
Power switch control Rated Voltage	AC 250V / DC 30V
Power switch control Rated Current	3 A
Product Size	144 x 94.8 x 20 mm (5.67 x 3.73 x 0.79 in)
Product Weight	164.4 g (0.36 lbs.)

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it