

HYPER BASS 12A

900 WATT BASS REFLEX ACTIVE SUBWOOFER

Hyper Bass series is the result of years of experience gathered by Soundsation in Portable Sound systems. These active subwoofers are equipped with 12", 15" or 18" high-excursion woofers. Sturdy and stylish birch plywood enclosures with full metal grille and acoustic foam ,offers a pleasant look and ensure an high quality sound and punch. Equipped with a Class D amp and switching power supply they deliver massive power up to 1200W with great efficiency. All models feature a stereo active crossover and balanced Input/Output/Link connections . All models feature M20 speaker pole mount, 2 or 4 recessed handles (12"or 15-18") 4 wheels predisposition on 15" and 18" version for portable sound purposes and easy carriage.

HYPER BASS 12A

56b1daa5-9073-48e1-91eb-d5235bc6684f.jpg

9274d733-1a7d-40bf-9f85-1b9677a75a7d.jpg

HYPER BASS 12A

900 WATT BASS REFLEX ACTIVE SUBWOOFER

PRODUCT DETAILS

KEY FEATURES

Bass-reflex Active Subwoofer

12" woofer

900 Watt class D amplifier

Integrated active crossover

XLR L/R Balanced Line Inputs

XLR L/R Balanced Filtered Outputs, XLR L/R Balanced Link Outputs

Controls: Sub Level, 80-120Hz crossover switch, 0-180° Phase, Shape switch, Ground Lift On-Off

RMS, Overload, Thermal limiter protection

Multiplex Birch plywood enclosure with painted black finish

2 lateral recessed handles

M20 type speaker pole mount to reduce vibrations

Dimensions (LxHxW): 480 x 480 x 560 mm

Weight: 17 Kg

SPECIFICATIONS

Bass reflex active subwoofer

Woofer 12", 3" voice coil

Amplifier 900W Peak/ 450W RMS, Class-D

Max SPL(Peak) 120dB

Crossover Frequency 120 Hz (24dB/Oct.)

Frequency Response [- 10dB] From 40 Hz to 150 Hz

HYPER BASS 12A

900 WATT BASS REFLEX ACTIVE SUBWOOFER

Frequency Response [- 3dB]	From 50 Hz to 120 Hz
LEDs	Power On (Green), Signal (Green) / Limit (Red)
Power Requirement	230Vac - 50 Hz
Minimum Power Consumption	500W
Power Connector	VDE with T5AL-250V Fuse
Dimensions (LxHxW)	480 x 480 x 560 mm
Weight	17 Kg