

Air 8 is an 8" + 1" coaxial speaker with a rigid, lightweight fiberglass cabinet, ideal for premium installations. It delivers detailed, linear sound, a wide 90°x90° coverage, and a peak output of 121 dB, with extended response from 70 Hz to 20 kHz and 95 dB sensitivity (1W/1m). The internal 2 kHz crossover ensures smooth transitions, while the compact design and custom finishes make it perfect for lounge bars, restaurants, clubs, and upscale residential spaces. Includes wall mount and Phoenix connector with Link Out for easy multi-speaker setups.















HIGHLIGHTS



LOW-RESONANCE FIBREGLASS COMPOSITE CONSTRUCTION

The use of **fibreglass material** ensures a **rigid and stable enclosure**, minimizing cabinet resonance and contributing to **clearer and more accurate audio reproduction**.

HIGHLY REFINED, SPECIALIST COMPONENTS

Highly refined and specialist in-house designed components reinforce the Air 8's position in the pro audio market. A popular choice for high-end venues with its sleek composition, this multifaceted product encompasses the best of modern innovation.







CUSTOM COLORS AVAILABLE UPON REQUEST

In addition to the 3 iconic Void brand colors -red, white and black- Air 8.1 can be produced in several other custom colors (the colors visible in the image are examples for illustrative purposes)



PRODUCT DETAILS

KEY FEATURES

Compact two-way 8" coaxial design: the 8" coaxial driver with integrated 1" tweeter ensures a point source of sound, providing a consistent and linear response throughout the frequency range.

Optimized 90° x 90° dispersion: the wide angle of coverage allows even sound distribution in rooms of various sizes, increasing clarity even in acoustically complex situations.

Ideal for fixed installations in upscale environments: with its elegant and discreet design, Air 8 is perfect for bars, restaurants, clubs, lounges, and even upscale residential settings.

Wall bracket included: the system comes with Air 8 mounting bracket for easy and secure installations, with several placement options.

SPECIFICATIONS

Frequency Response	70 Hz - 20 kHz ±3 dB
Efficiency	95 dB 1W/1m
Crossover Points	2 kHz passive
Nominal Impedance	8?
Power Handling	300 W AES
Maximum Output	119 dB cont, 121 dB peak
Driver Configuration	1 x 8", 1 x 1" coaxial
Dispersion	90°H x 90°V
Connectors	Phoenix
Weight	6.2 kg (13.2 lbs)
Enclosure	Fibreglass composite





Mounting Air 8 wall b	racket (supplied)
-----------------------	-------------------

Colors Black (custom colours available upon request)

Dimensions (W x H x D) 300mm x 419mm x 179mm

