

INTERVIEWER

OMNIDIRECTIONAL INTERVIEW MICROPHONE WITH STURDY CASING AND COMFORTABLE GRIP

Lewitt Interviewer is an extremely sturdy dynamic microphone featuring an omnidirectional polar pattern. Its capsule is INTERVIEWER fully rubber mounted. In combination with the INTERVIEWER new coating technology, all handling noise is reduced to a minimum while offering safe and comfortable grip. With the purpose-built Dust Protection Membrane and its heavily rugged, most resilient housing, the INTERVIEWER is the perfect companion even under the roughest conditions. Tailored for voice reproduction the INTERVIEWER provides you with crystal clear results in almost any situation. This hassle-free tool makes it easy to concentrate on what is essential, that is "now." With the purpose-built Dust Protection Membrane and rugged housing, the INTERVIEWER will be the perfect companion even under the roughest conditions. refined rubber suspensions provide the best possible dampening of unwanted structure-borne noise caused by hand-movement and decouples the capsule from the casing. New coating materials reduce all handling noise even more while offering safe and comfortable grip.

[37dee7d7-9706-421c-aec9-8d91be5d40f1.jpg](#)

[6c08d735-23fa-473c-9ae6-5c3da59966da.jpg](#)

[44cb7c5d-eecc-4459-b519-6b5a5b5a5b5a.jpg](#)

INTERVIEWER OMNIDIRECTIONAL INTERVIEW MICROPHONE WITH STURDY CASING AND COMFORTABLE GRIP

PRODUCT DETAILS

KEY FEATURES

THE PERFECT COMPANION - Durable and withstanding

Great speech intelligibility, Omnidirectional dynamic capsule - no proximity effect, no off-axis muddiness, Linear frequency response

Professional look and feel - connect it to your camcorder or DSLR

Sturdy and resilient

Handling noise reduced to a minimum

High brand visibility thanks to Customisable mic flag

Comes with DTP 40 Lb Leather bag, Customable Microphone flag, Camera connection cable (XLR 3 pin F to 3,5mm minijack stereo), windscreen

SPECIFICATIONS

Type	Dynamic, moving coil
Polar pattern	Omnidirectional
Sensitivity	1.33 mV/Pa, -57.58 dBV/Pa
Internal impedance	235 Ohm
Rated load impedance	1000 Ohm
Connector	gold plated 3-pin XLR
Microphone dimensions	wiremesh ø - 36 mm handle ø - 22 mm total length - 272.7 mm , wiremesh ø - 1.42 in handle ø - 0.87 in total length - 10.74 in Microphone
Net weight	250 g, 8.82 oz