

0993940921

AMERICAN PROFESSIONAL II TELECASTER NECK, 22 NARROW TALL FRETS, 9.5" RADIUS, ROSEWOOD

0993940921

Crafted in the same facility as our U.S.-made instruments, the American Professional II Telecaster Neck draws from more than sixty years of innovation, inspiration and evolution to meet the demands of today's working player. Our popular Deep "C" neck now sports smooth rolled fingerboard edges and a "Super-Natural" satin finish that provides a supremely comfortable feel. Other features include a 9.5"-radius maple or rosewood fingerboard, bone nut and 22 narrow-tall frets for easy bending.

The neck pocket has 4 offset pre-drilled pilot holes so if it is being installed on a standard body, a fifth pilot hole will need to be drilled.

This replacement neck is for a Fender® or Squier® by Fender guitar.

Because Fender genuine replacement necks have not been mounted to guitar bodies, nut slots must be cut by qualified personnel. Other installation processes may be required, such as fret work, fitting the neck to the neck pocket, and other instrument setup procedures. Your local FMIC Authorized Service Center can install genuine replacement necks

68b47b92-93a3-4039-aa56-7278be838970.png

1a98ea45-c0a9-4641-ae08-6dddf101ef0c.png

0993940921

AMERICAN PROFESSIONAL II TELECASTER NECK, 22 NARROW TALL FRETS, 9.5" RADIUS, ROSEWOOD

PRODUCT DETAILS

KEY FEATURES

Instrument Type: Telecaster®
Neck Material: Maple
Color: Natural
Neck Shape: Deep "C"
Fret Size: Narrow Tall
Number of Frets: 22
Truss Rod: Bi-Flex™
Nut Material: Bone
Neck Mounting: 4-Bolt Offset

SPECIFICATIONS

Fingerboard Radius	9.5" (241 mm)
Nut Width	1.685" (42.8 mm)
Scale Length	25.5" (648 mm)
Truss Rod Nut	1/8" Hex Adjustment
Neck Thickness	1st Fret - .820" (20.82 mm), 12th Fret - .920" (22.86 mm)
Tuner Mounting Config	Dual Guide Pin
Peg Hole Diameter	.404" (10.26 mm)
Headstock Thickness	.540" (13.71 mm)