

CVT320

NOVASTAR CVT300 FIBER CONVERTER

When it is necessary to cover a large distance between your Novastar controller and your LED display, the CVT320 fiber optic converter is the right solution.

The Novastar CVT320 can be used either as a transmitter or receiver unit. Thanks to the LC interface, the device can be connected very easily to a fiber optic source.

To transmit the signal from a controller to an LED-Display two units are always needed (Transmitter (TX) and Receiver (RX)). The Novastar CVT320 is plug and play and no other drivers are necessary.

CVT320

[98da9ae5-2e15-4707-b6f8-72658ba0630c.jpg](#)

[8cad71c0-c8d8-460a-a8a5-b3e841032f8b.jpg](#)

CVT320

NOVASTAR CVT300 FIBER CONVERTER

PRODUCT DETAILS

KEY FEATURES

Transmission distance of up to 15 Km

Plug & Play: no additional drivers required

1x Single-mode twin-core LC fiber connector

1x Ethernet port

LED indicators

SPECIFICATIONS

Input Voltage	AC 100-240V 50/60Hz
Rated Current	0.7 A
Rated Power Consumption	3.5W
Operating Temperature	from -20°C to +70°C
Storage Temperature	from -30°C to +80°C
Product Sizes	149.3 x 132 x 38 mm (5.88 x 5.20 x 1.50 in)
Product Weight	0.53 kg (1.17 lbs.)