
HYPER BASS 18A

1200 WATT 18" BASS REFLEX ACTIVE SUBWOOFER


Hyper Bass series is the result of years of experience gathered by Soundsation in Portable Sound systems. These active subwoofers are equipped with 12”, 15” or 18” high-excursion woofers. Sturdy and stylish birch plywood enclosures with full metal grille and acoustic foam ,offers a pleasant look and ensure an high quality sound and punch. Equipped with a Class D amp and switching power supply they deliver massive power up to 1200W with great efficiency. All models feature a stereo active crossover and balanced Input/Output/Link connections . All models feature M20 speaker pole mount, 2 or 4 recessed handles (12”or 15-18”) 4 wheels predisposition on 15” and 18” version for portable sound purposes and easy carriage.

HYPER BASS 18A

60b10377-e2c7-4141-865f-7fea9e218b96.jpg



daff543e-b644-43ff-8654-0f0003f21882.jpg



511c8f43-51dc-4e7e-a01a-08860f90b

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

HYPER BASS 18A

1200 WATT 18" BASS REFLEX ACTIVE SUBWOOFER

PRODUCT DETAILS

KEY FEATURES

- Bass-reflex Active Subwoofer
- 18" woofer
- 1200 Watt class D amplifier
- Integrated active crossover
- XLR L/R Balanced Line Inputs
- XLR L/R Balanced Filtered Outputs, XLR L/R Balanced Link Outputs
- Controls: Sub Level, 80-120Hz crossover switch, 0-180° Phase, Shape switch, Ground Lift On-Off
- RMS, Overload, Thermal limiter protection
- Multiplex Birch plywood enclosure with painted black finish
- 2 lateral recessed handles each side
- M20 type speaker pole mount to reduce vibrations
- Predisposition for 4 wheels (not included)

SPECIFICATIONS

Bass reflex active subwoofer	
Woofer	18”, 4” voice coil
Amplifier	1200W Peak/ 600W RMS, Class-D
Max SPL(Peak)	126dB
Crossover Frequency	120 Hz (24dB/Oct.)

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

HYPER BASS 18A

1200 WATT 18" BASS REFLEX ACTIVE SUBWOOFER

Frequency Response [- 10dB]	From 30 Hz to 150 Hz
Frequency Response [- 3dB]	From 35 Hz to 120 Hz
LEDs	Power On (Green), Signal (Green) / Limit (Red)
Power Requirement	230Vac - 50 Hz
Minimum Power Consumption	750W
Power Connector	VDE with T5AL-250V Fuse
Subwoofer Size (LxHxW)	630 x 670 x 540 mm
Subwoofer Weight	45 Kg
Packing Size (LxHxW)	700 x 775 x 630 mm
Gross Weight	51 kg

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it