

MTP 740 CM

LIVE AND STUDIO CONDENSER MICROPHONE

The MTP 740 CM uses the same large-diaphragm condenser capsule as the LEWITT performance flagship MTP 940 CM. It's the same 1-inch capsule as in our studio microphones - that leads to a natural, authentic sound with first-class transient response due to the ultra-thin, gold-layered, low-mass, 1-inch diaphragm. The MTP 740 CMs top-applications are vocal performances on stage and in the studio. As a straight forward vocal performance microphone it features a cardioid polar pattern which ensures effective rear sound rejection both onstage and in the studio. Thanks to advanced suspension technology – capsule and electronics are fully rubber-cushioned – the MTP 740 CM is shock-resistant and offers a highly effective structure-borne noise elimination. With its two step pre-attenuation and the switchable low-cut setting the MTP 740 CM can be adjusted to various vocal requirements and recording situations. In short: the MTP 740 CM has everything on board for the most demanding live and studio vocal performances and recordings. Pure large-diaphragm studio condenser sound and features on stage and stage feeling for authentic vocal studio recordings!

MTP 740 CM

MTP 740 CM

LIVE AND STUDIO CONDENSER MICROPHONE

PRODUCT DETAILS

KEY FEATURES

Uncompromising large-diaphragm studio condenser sound for stage performances routines

3 micron thin gold layered Mylar diaphragm

Cardioid polar pattern for clean live sound and effective rear rejection

Integrated acoustic pop and windshield for excellent protection without compromising high-frequency clarity

Highly shock-resistant and effective structure-born noise elimination thanks to advanced suspension technology

Rock-solid, full-metal die-cast body for rough daily touring

Hardened spring steel mesh grille to prevent wear and abuse

Superior dynamic range of 140 dB (A)

Exceptionally low self-noise of 15 dB (A)

SPL max of 165 dB (A) for 0,5 % THD

2-step attenuation, 2-position low-cut

Illuminated setting indication for quick and easy handling in dark environments

Top applications: Authentic and dynamic live vocal performances, Handheld vocal studio recordings , Acoustic instruments (live & studio), Jazzy snare drum and percussion instruments

SPECIFICATIONS

Acoustical operating principle	Pressure gradient transducer, externally polarized
Diaphragm	3 micron gold sputtered Mylar
Transducer Ø	25.4 mm / 1 inch
Polar pattern	cardioid
Frequency range	20 to 20,000 Hz

MTP 740 CM

LIVE AND STUDIO CONDENSER MICROPHONE

Sensitivity	9 mV / Pa (-41 dBV)
Signal / noise ratio	79 dB (A)
Equivalent noise level	14 dB (A) according to IEC 60268-1
Dynamic range of FET mic. Amp.	138 dB (A)
Max SPL for 0,5 % THD	153 dB, 0 dB pre-attenuation / 163 dB, 10 dB pre-attenuation
Pre-attenuation pad	10 dB, switchable
Low-cut	6 dB / octave at 80 Hz
Rated impedance	< 150 ohms
Rated load impedance	> 1.000 ohms
Supply voltage	48 V +/- 4 V
Current consumption	5.5 mA
Enclosure	Zinc die cast
Connector	Gold plated 3-pin XLR
Dimensions	51 dia. x 183 mm (2 dia. x 7.2 inch)
Net weight	332 g (11.71 oz)