

LCT240PRO

SINGLE-PATTERN MICROPHONE WITH HIGH-PERFORMANCE CAPSULE FOR ALL APPLICATIONS

The LCT 240 PRO is an extremely versatile cardioid condenser microphone designed for everyone who's eager to take the next step in professional recording. Equipped with a high-performance condenser capsule it enables clean, modern, and detailed recordings. To accomplish an intimate and direct sound, especially on vocals, we have added a boost on the airy frequencies. The sturdy, compact and streamlined housing comes in chilly white and classic black. Be prepared for fantastic results on vocals, acoustic instruments, amplifiers, drums, piano, ... - at home, in the studio and on stage - fast and uncomplicated

LCT240PRO

36fb8bd5-8d56-49fe-b753-919bcccefb42.jpg

00c65462-a5aa-402c-aa1b-ef771ce93773.jpg

13e63973-307a-4907-943d-16d4d8

f1a32e42-ebd4-4054-8aa1-7d3b42c99d98.jpg

f61573dd-e0a8-4fa9-aa6a-6aeadc8e6e4e.jpg

d924e2fb-a26a-47e9-bf9b-bafc08c

LCT240PRO

SINGLE-PATTERN MICROPHONE WITH HIGH-PERFORMANCE CAPSULE FOR ALL APPLICATIONS

PRODUCT DETAILS

KEY FEATURES

Fantastic sound - on all sound sources

Handles even the highest sound pressure levels

What's in the box: use the leatherette bag to protect your mic from dust and scratches. The windshield comes in handy for outdoor gigs, vocal recordings, or simply to protect the capsule from moisture.

SPECIFICATIONS

Type	Condenser, permanently polarized
Acoustical operating principle	Pressure gradient transducer
Transducer	Ø 17 mm, 0.67 in
Polar pattern	Cardioid
Sensitivity	16.7 mV/Pa, -35.5 dBV/Pa
Equivalent noise level	19 dB (A)
Max SPL for 0.5 % THD	142 dB
Dynamic range	123 dB (A)
Internal impedance	100 Ohms
Rated load impedance	1,000 Ohms
Supply voltage	48 V +/- 4 V
Current consumption	3.1 mA
Connector	Gold plated 3-pin XLR

LCT240PRO

SINGLE-PATTERN MICROPHONE WITH HIGH-PERFORMANCE CAPSULE FOR ALL APPLICATIONS

Microphone dimensions

138 x 52 x 36 mm, 5.43 x 2.04 x 1.42 inch

Microphone net weight

310 g / 10.9 oz