

SESSIONMIX 1622

16 CHANNEL PROFESSIONAL MIXING CONSOLE WITH MEDIA & BLUETOOTH

Using the foundation of our popular CLUBXS16+, enhancing the design style and adding a stereo sub-group. The SessionMix 1622 gives you 14 Mic Channels and 1 Stereo Channel in a compact space saving design.

With the features available, such as USB recording, or the Bluetooth playback ability, there are many applications whether a small to medium size band or an installation where the channel count is important.

60mm faders on all channels, balanced XLR outputs, PFL/Listen on every channel and professional mic/line inputs make the new SessionMix series worth having a closer look at.

SESSIONMIX 1622

70257233-f57e-4518-b20f-01eb48cf9125.png

e56e59c4-d89a-4f41-83de-12e695251b26.png

905ae129-e80e-42e3-96cb-07dc8

SESSIONMIX 1622

16 CHANNEL PROFESSIONAL MIXING CONSOLE WITH MEDIA & BLUETOOTH

PRODUCT DETAILS

KEY FEATURES

16 channels with 14 Mic Inputs and 1 Stereo Channel

USB/SD Card/Bluetooth media module for Playback / Recording

Stereo Sub Group with 60mm Faders and Jack Outputs

16 Selected and High-quality DSP effects with Reverb, Delay and Stereo Effects

DSP On/Off Footswitch Socket to easily turn On or Off your effects

Compressor and 80Hz High-Pass Filter on all Mic Channels

PFL and Mute on all Channels

3-band EQ on Mic channels for superior tone adjustments

2-band EQ on Stereo channel to add warmth to your instruments

2 x Aux & 1 x DSP Outputs for External Monitors and FXs

Stereo Return Extra Inputs with Level Control

RCA/Phono Playback and Record ability

Headphones and Control Room Output for full Monitoring

+48v Phantom Power on Mic Channel for condenser microphones

External PSU for reliable noise free operation

SPECIFICATIONS

Inputs	16
Mic Input channels	14

SESSIONMIX 1622

16 CHANNEL PROFESSIONAL MIXING CONSOLE WITH MEDIA & BLUETOOTH

Stereo Input channels	1
Sub Group / output	2
Mic Gain	from +6dB to -50dB
Line Gain	from +10dB to -34dB
EIN	-100dB
Frequency response	10Hz – 20kHz
THD Mic Channel	±0.03%
Signal to Noise Ratio	80dB
Output Levels	Max +26dB (Balanced) / Max +20dB (Unbalanced)
Channel EQ	Hi 12kHz, Mid 2.5kHz, Low 45Hz
Low-Cut Filter	80Hz
Compression	Ys, on all Mic Inputs
Media Player	MP3/USB/SD/BT Audio Playback
Recording	USB/SD Audio Recording
DSP Effects	16 Effects with Selection knob and 1 Adjustable Parameter
Power requirements	External 12V DC Adapter
Dimensions (WxHxD)	602,6 x 152 x 467,5 mm