Q-AIR Mini

BATTERY POWERED PAR 4X12W RGBWAUV

Q-AIR Mini

PORTRAIT Q-Air Mini is a battery-powered (or mains-powered) PAR, specifically designed for rental applications. You can easily control it by choosing among IR remote control, wired DMX-512 connection, Wireless DMX (by using the **AIRCOM-126**, 2.4GHz Wireless DMX Transceiver for further details), Auto Run, Master/Slave, Sound Active control. The lighting emitting system consists of 4pcs 12W RGBWA+UV 6in1 high-brightness LEDs with a life-span of approximately 50,000 hours. Each LED features a high-quality lens with 15° beam angle and 29° field angle, making this PAR ideal for wash use.

The **PORTRAIT Q-Air Mini** has a highly compact housing, and can be fit inside 300x300mm truss to create wonderful wash effect inside the truss structure. The fixture can sit on even and solid floor and work as an up-light. It also has a built-in adjustable tilt support. By pushing the tile support, the fixture tile can move up to 25° to wash walls or facades.

The high-efficiency lithium battery guarantees a complete charge from zero within about 5 hours, and a working duration ranging from 4 hours (full color mode) to 15 hours (single color mode). The infrared remote control allows remote control of the main functions without the use of DMX.

BAG NOT INCLUDED

a997c009-ce6f-48f0-ade3-0ad24f55d11a.jpg 3939cc74-0ec5-4719-ac0c-fe933ec0ac55.jpg 03748af8-0bf7-4a9c-b12e-b90ad400


DMX-512 Control Battery Powered Wireless Control No Fan

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

Q-AIR Mini

BATTERY POWERED PAR 4X12W RGBWAUV

HIGHLIGHTS




DISPLAY LED AND WIRELESS DMX, CONTROL IN MAXIMUM FREEDOM

If for aesthetic or distance issues the normal DMX cable connection is not for you, no problem. Portrait Q-Air fixtures can be controlled **up to 300m** without cables thanks to **2.5GHz Wireless DMX**, which operates in the license-free ISM band from 2.400 to 2.525 GHz and adopts the highly efficient **GFSK modulation system**. This protocol provides **7 IDs, each with 512 DMX channels**, and is a fast and safe solution even in rather complex projects.

But there is more. If your DMX controller and the rest of your other fixtures do not have the Wireless protocol, DMX, you can always pair it with Soundsation's **AIRCOM-126**, a wireless transmitter/receiver compatible with all wireless systems on the 2.4GHz band. In this way your control unit can manage your sets completely wirelessly or hybrid, greatly reducing the number of DMX cables.

ADJUSTABLE TILT STAND 0°-25°


The 0° to 25° adjustable bracket allows the product to illuminate any vertical surface, whether near or far from the product itself, making it flexible for any use for rental or temporary installations.



Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

Q-AIR Mini

BATTERY POWERED PAR 4X12W RGBWAUV



4 HIGH-EFFICIENCY RGBWAUV LED

6-colour **RGBWAUV** technology

The addition of Amber, White and UV to the basic RGB colours allows for an infinite palette of colours, enabling the product to flawlessly blend colours and make them ever more vivid and performing.

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

Q-AIR Mini

BATTERY POWERED PAR 4X12W RGBWAUV

PRODUCT DETAILS

KEY FEATURES

- 4x 12W RGBWA+UV LED 6in1 high-efficiency and long-life
- Beam angle 15°
- Field angle 29°
- CRI ? 9090
- Wireless 2.4 GHz DMX-512 control
- DMX 512 standard wired control RJ45/XLR
- Display LED with intuitive interface
- Rechargeable Lithium-Ion Battery for up to 15-hour operation
- 0°-25° adjustable tilt support
- Independent Electronic Strobe, 0-20 times per second with adjustable speed.

SPECIFICATIONS

Light sources	4x 12W RGBWA+UV
Beam angle	15°
Field angle	29°
Led average life span	50.000 hours
Control mode	DMX512, Master/Slave, Stand Alone, Wireless DMX, IR Remote Control control
DMX channel	6CH / 10CH
Control panel	LED Display
Power input	100-240VAC 50/60Hz
Power consumption	Max. 55W

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

Q-AIR Mini

BATTERY POWERED PAR 4X12W RGBWAUV

Power In connection	5.5mm Input
Battery type	Rechargeable lithium-ion battery pack
Charge time	About 5.0 hours
Battery life	up to 15 hours at running single color
Working temperature	-10°C – 45°C
Charging temperature	0°C – 35°C
IP rating	IP20
Cooling	Natural cooling, silent operation
Housing material	Rigid metal
Housing color	Black
Fixture size (WxDxH)	34 x 134 x 130 mm
Net weight	1.9 kg
Carton size (WxDxH)	180 x 175 x 200 mm
Gross weight	2.5 kg

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it