

GG6

6.5" TWO-WAY FULL-RANGE PASSIVE SPEAKER (BLACK)

GG6 is a 6.5" two-way full-range speaker designed to deliver high-quality audio performance in commercial environments, both indoors and outdoors. Its compact and lightweight design, combined with a discreet look, makes it ideal for restaurants, hotels, retail spaces, conference rooms, and corporate settings.

The 6.5" ferrite magnet woofer ensures a powerful reproduction of mid and low frequencies, while the 1" aluminum dome tweeter delivers crisp and detailed highs. The weather-resistant ABS enclosure (IP56 rated) and the included wall-mounting bracket make installation easy in any setting.

On the rear panel, a 70/100V transformer with line selector allows use in both high and low impedance systems, making the GG6 extremely flexible and suitable for large-scale installations.

GG6

[22d91f52-a4b1-44b6-b8c9-d88f0e5d67ea.jpg](#)

[04fd6bea-1022-4d25-8500-b550d15ba961.jpg](#)

70V-100V Line 2-Way Speaker IP56

GG6

6.5" TWO-WAY FULL-RANGE PASSIVE SPEAKER (BLACK)

HIGHLIGHTS



MAXIMUM ADAPTABILITY FOR EVERY TYPE OF INSTALLATION

Thanks to the integrated 70/100V transformer with power selector switch (2/4/8/16/32W), the GG6 can be connected to several loudspeakers in parallel while maintaining high energy efficiency. It is the perfect solution for those looking for a compact, durable loudspeaker with excellent sound quality, easily adaptable to different environments and application scenarios.

GG6

6.5" TWO-WAY FULL-RANGE PASSIVE SPEAKER (BLACK)

PRODUCT DETAILS

KEY FEATURES

- 6.5" woofer and 1" aluminium dome tweeter for a defined and powerful sound
- ABS housing with IP56 protection rating, also ideal for outdoor installations
- Compact and lightweight design, easy to mount with bracket included

SPECIFICATIONS

Type	Passive loudspeaker
Transducers	6,5" ferrite magnet PP woofer 1" aluminum dome tweeter
Frequency Response	50 Hz - 20 kHz (-6dB)
Max SPL	115 dB
Rated Power	160W 2/4/8/16/32W @70/100V
Coverage	V. 90° H. 90°
Connectors	Screw type terminals
Nominal Impedance	Low 8 Ω Hi-Z 70V-100V
Dimensions (W x H x D)	193x310x180 mm (7.6x12.2x7.0 in)
Weight	2,8 kg (6.17 lb)
Material	ABS
Colors	Black
IP Rating	IP56