

VX1000

ALL-IN-ONE VIDEO CONTROLLER AND PROCESSOR

The VX1000 is Novastar's new all-in-one controller that integrates video processing and video control capabilities into one box.

It features 10 Ethernet ports and supports Video Controller, Fiber Converter and Bypass working modes. One VX1000 unit can drive up to 6.5 million pixels, with the maximum output width and height up to 10,240 pixels and 8192 pixels, respectively, ideal for ultra-wide and ultra-high LED screen applications.

The VX1000 is capable of receiving a variety of video signals and processing 4Kx1K@60Hz high-resolution images. Furthermore, the device features stepless output scaling, low latency, 3D, pixel-level brightness and chroma calibration and more, to present you with an excellent image display experience. What's more, the VX1000 can work with Novastar's supreme software NovaLCT and V-Can to greatly facilitate your in-field operations and control, such as screen configuration, Ethernet port backup settings, layer management, preset management and firmware update.

Thanks to its powerful video processing and sending capabilities and other outstanding features, the VX1000 can be widely used in applications such as medium and high-end rental, stage control systems and fine-pitch LED screens.



VX1000

ALL-IN-ONE VIDEO CONTROLLER AND PROCESSOR

PRODUCT DETAILS

KEY FEATURES

Powerful video processing based on SuperView III image quality processing

Maximum loading capacity of 6.5 million pixels

4K x 1K@60Hz high-resolution images processing capabilities

Multiple control modes: V-Cam, NovaLCT, front panel

Mosaic input source supported

Three working modes: Video Controller, Fiber Converter, Bypass

Adjustable layer size, position and priority

Multiple kinds of hot backup

Output synchronization of multiple units

Up to 4 units can be cascaded for image mosaic

All-round color and brightness adjustment

Pixel level brightness and chroma calibration

Easy preset saving and loading

3D function

SPECIFICATIONS

1x 3G-SDI input with max. resolution of 1920x1080@60Hz + Loop output

2x HDMI 1.4 input with max. resolutions of 3840x1080@60Hz or 3840x2160@30Hz, + 1x Loop output and custom resolutions supported

VX1000

ALL-IN-ONE VIDEO CONTROLLER AND PROCESSOR

2x DVI inputs with max. resolutions of 3840x1080@60Hz or 3840x2160@30Hz, + 1x Loop output and custom resolutions supported

10x Gigabit Ethernet output ports with max. loading capacity of 6.5 million pixels. Port 1 and 2 support audio output

1x HDMI 1.3 output with adjustable resolution

2x 10G optical fiber ports. Max capacity of OPT 1: 1x 4Kx1K@60Hz or 2x 2Kx1K@60Hz. OPT 2: for output only

1x Ethernet control port for connection to PC or router

1x USB 2.0 Type-B port for PC connection or input for cascading devices

1x USB 2.0 Type-A output connector for cascading devices

1x Genlock port + Loop for connection to an external sync signal

Input Voltage 100-240V~, 50/60Hz

Rated Power Consumption 28W

Working Temperature from 0°C to 45°C

Working Humidity 20% RH to 90% RH, non-condensing

Noise Level (at 25°C/77°F) 45 dB (A)

Product Size 483.6 mm x 351.2 mm x 50.1 mm (19.4 x 13.82 x 1.97 in)

Product Weight 4 kg (8.82 lbs.)