

GH4AW

ULTRA-COMPACT 4' FULL RANGE ACTIVE SATELLITE SPEAKER (WHITE)

The GH4A is a compact active satellite speaker designed for professional applications requiring clear and directional sound, even in acoustically challenging spaces. It features a 60W Class D amplifier, allowing it to power an additional KGEAR passive speaker or subwoofer, reducing external components.

Its 4" full-range driver with dual-coil neodymium magnet ensures accurate and powerful audio. The optimized enclosure minimizes rear emission, increasing system efficiency. Stainless steel build with IP64 rating (with G-IPCAP1) makes it suitable for indoor and outdoor use.

Equipped with Phoenix connectors, DC 24V input, audio output, mute contact, and auto ON/OFF function. Wall-mountable via GF-WALL bracket, and usable alone or in array configurations.



GH4AW

ULTRA-COMPACT 4' FULL RANGE ACTIVE SATELLITE SPEAKER (WHITE)

HIGHLIGHTS

BUILT-IN AMPLIFICATION



The integrated amplifier allows you to drive a second speaker or passive subwoofer. This greatly simplifies installation, reduces the number of components required and makes it perfect for compact, elegant and highly efficient solutions.

WEATHER-RESISTANT CONSTRUCTION

The GH4A rugged durability is due in part to its weather-resistant construction: the compact stainless steel cabinets is built to withstand the rigors of touring and permanent installation, providing added peace of mind.



GH4AW

ULTRA-COMPACT 4' FULL RANGE ACTIVE SATELLITE SPEAKER (WHITE)

PRODUCT DETAILS

KEY FEATURES

Wall Mount Included: The GF-WALL swivel mount is included for easy and precise installation.

Compact design, high performance: 4" full-range driver with dual-frequency neodymium magnet

Reduced Rear Emission: the optimised cabinet design reduces rear dispersion, improving sound directionality and reducing unwanted reflections.

Wall Mount Included: The GF-WALL swivel mount is included for easy and precise installation.

SPECIFICATIONS

Type	Active loudspeaker
Transducers	4" neodymium magnet full-range driver
Frequency Response	150 Hz - 20 kHz (-6dB)
Max SPL	116 dB
Rated Power	140 W
Coverage	V. 90° H. 90°
Connectors	2x Phoenix connector (4-pin euroblock), Balanced Line in, Mute contact Power out, 24V DC IN (power supply not included)
Mains Connector	4PIN Euroblock, 2x Phoenix 1,5/ 4-ST-3,81 compatible
Nominal Impedance	4 ?
Amp Module	1-channel Class-D audio amplifier
Output Power	100W @ 2? (24V power)

GH4AW

ULTRA-COMPACT 4' FULL RANGE ACTIVE SATELLITE SPEAKER (WHITE)

Power Consumption 30W Rated Load 1/8 Max Power**Protections** Thermal Protections (Power limiting - Thermal Shutdown), Short-circuit/overload output protections**Operating Range** 12-24 V DC**Dimensions (W x H x D)** 112x112x94 mm (4.41x4.41x3.70 in)**Weight** 1,2 kg (2,65 lb)**Material** Stainless steel**Colors** White**IP Rating** IP64 (G-IPCAP1 accessory required)