

VOXTAKER 100 USB

CONDENSER STUDIO MICROPHONE WITH CARDIOID POLAR PATTERN AND USB INTERFACE

VoxTaker 100 USB is a plug and play condenser studio recording microphone, without having to install any driver. Like the VoxTaker 100, it is a professional microphone featuring true condenser capsule with cardioid polar pattern. It can be used with confidence in a variety of professional applications, such as recording studios, broadcasting, podcasting, and stage performances just connecting a USB cable. It is compatible with all recording software and ASIO audio drivers. It uses high-performance USB chip technology and high-quality single-point capacitive transducers. That's why the VoxTaker 100 USB has very low self-noise and high output to reproduce even the subtle sound and fulfil the requirement of high sound quality for broadcasting and recording. The package includes Shock-Mount, Pop Filter and USB cable, all inside a plastic case.

VOXTAKER 100 USB

8e48dd21-45d8-4205-b80b-b26466707da2.jpg

ea662f4e-874b-4a02-84be-db8db24bd13b.jpg

326b44f7-aa94-43f0-a6b1-e41a2

VOXTAKER 100 USB CONDENSER STUDIO MICROPHONE WITH CARDIOID POLAR PATTERN AND USB INTERFACE

PRODUCT DETAILS

KEY FEATURES

Professional Pressure Gradient Transducer

Cardioid Polar Pattern

High Quality FET Preamp

Strong Output Signal without Distortion

High-speed AD/DA conversion technology

44.1/48 kHz Sample Frequency

16 Bit Resolution

USB 2.0 Plug and Play Operation

Maximum compatibility with all Operative Systems without any drivers

Low Power Consumption

High Absorption Shock-mount

Stylish and Innovative Pop Filter

Package includes Plastic Case and USB cable

SPECIFICATIONS

Element	16mm high-sensitivity condenser capsule
---------	---

Cardioid Polar Pattern

Frequency Response	30Hz -20kHz
--------------------	-------------

Sensitivity	-34dB (0dB = 1V/Pa at 1kHz)
-------------	-----------------------------

VOXTAKER 100 USB CONDENSER STUDIO MICROPHONE WITH CARDIOID POLAR PATTERN AND USB INTERFACE

Max Input SPL	130dB (at 1kHz 1% T.H.D.)
16bit A/D-D/A conversion resolution	
Stereo ADC/DAC operation	
USB 2.0 transceiver	
ADC sampling frequency	8k, 11.025k, 16k, 22.05k, 32k, 44.1k, 48kHz
ADC THD+N = 0.01%	
ADC S/N Ratio = 89dB	
ADC Dynamic Range = 89dB	
DAC frequency	32k, 44.1k, 48kHz
DAC THD+N = 0.005%	
DAC S/N Ratio = 96dB	
DAC Dynamic Range = 93dB	
Stereo output power	400mW
Microphone Size (WxHxD)	188x50x50 mm
Microphone Weight	252 g
Case Size (WxHxD)	340 x 280 x 90 mm
Package Weight (Mic., case and accessories)	1.5kg