


CL-XLR5DMX-20

DMX CABLE XLR 5 PIN (20 MT)

CENTOLIGHT DMX cables are designed for professional AVL (Audio, Video, and Lighting) applications, providing reliable signal transmission for lighting control systems. Manufactured with high-quality materials, these cables ensure low interference, maximum signal integrity, and durability.

They are ideal for use in stage productions, concerts, theaters, and fixed installations where a stable and precise DMX signal is crucial.

CL-XLR5DMX-20



CL-XLR5DMX-20

DMX CABLE XLR 5 PIN (20 MT)

PRODUCT DETAILS

KEY FEATURES

Professional DMX cable built with the best materials

O.F.C construction

High quality jacket PVC ensures unmatched durability

Flexible, easy winding

Applications: productions, concerts, theaters, and fixed installations

Lenght: 20 mt

SPECIFICATIONS

Connector	XLR 5 PIN	
PVC diameter	6.5 mm	
No. of inner conductors	2x0.34 mm ²	
Copper strand per conductor	7x0.25 mm	
Conductor insulation	PE 1.70 mm	
Shielding	copper spiral shielding with 80 x 0.10 mm + AL/PT-foil + PE filter	
Shielding factor	100%	
Capac. cond./cond. per 1 m	52 pF	
Capac. cond./shield. per 1 m		105 pF
Cond. resistance per 1 m		55 m?
Shield. resistance per 1 m		27 m?