

SENSE12A+ 12" ULTRA-COMPACT ACTIVE COAXIAL STAGE MONITOR

Sense A+ stage monitoring speakers feature Coaxial HF and LF units for increased sensitivity and true production of tone, with NdFeB magnetic HF compression drivers, dual Class-D amplifier circuit, 1200W (Peak Power, DSP processing and a 43degree monitoring angle all in a sleek, compact, lightweight design.

SENSE12A+

[e2171b92-7e1c-40dc-85b0-62ed1ca7648b.png](#)

[1b7bdeab-6117-4199-845e-b94b214403b3.png](#)

SENSE12A+ 12" ULTRA-COMPACT ACTIVE COAXIAL STAGE MONITOR

PRODUCT DETAILS

KEY FEATURES

- Coaxial Design with Neodymium HF Components
- 43 Degree Wedge Angle for Ideal Close Monitoring Position
- Built-in 24bit/48kHz DSP with EQ, Live or Monitor Modes, Delay
- Modes Preset Tuning to use as either a Monitor or PA Cabinet
- 1200W Class-D High Performance Power Amp Modules
- Ultra-Compact Footprint from Coaxial Design
- 35mm Top Hat Socket to Use as PA Cabinet or Side-Fill
- Strong and Durable Steel Grille to take the strain
- Anti-Scratch Black Painting

SPECIFICATIONS

Cabinet Type	2-Way Coaxial Active
Frequency Response	55Hz - 20kHz
Max SPL	127dB
Input Sensitivity	0dBu
Amp Peak	1200W
Amp PGM	600W
Amp RMS	300W (260+40)
LF Driver	12" / 65 mm V.C.

SENSE12A+

12" ULTRA-COMPACT ACTIVE COAXIAL STAGE MONITOR

HF Driver	1.75" / 44 mm V.C.
Coverage (h x v)	80 x 80 degree
Crossover frequency	2.4kHz
Connection	2 x XLR / Jack Input + 3.5mm, XLR Output
Dimensions (WxHxD)	335 x 545 x 319mm
Weight	14.5kg