

MCR2022-100

BULK BALANCED MICROPHONIC CABLE (100 MT)

Bulk balanced microphonic cable (100 mt) featuring high conductivity. OFC (Oxygen Free Copper) technology, 95% shielding, 2x0,22mm² section, 6mm diameter.

MCR2022-100

62c267e6-5ff9-47f0-b0b9-e305d9bd374d.jpg

MCR2022-100

BULK BALANCED MICROPHONIC CABLE (100 MT)

PRODUCT DETAILS

KEY FEATURES

- Balanced microphonic cable
- OFC construction (Oxygen Free Copper)
- High conductivity
- Mt: 100

SPECIFICATIONS

OFC construction (Oxygen Free Copper)		
Shielding	95% with spiral copper 80x0,10 mm	
Inner conductors	2x0,22 mm2	
Copper strand per conductors	28x0,10 mm	
Diameter	6 mm	
Jacket	PVC	
Temp. range	-20(min)/70 (max)	
AWG	24	
Capac. cond/cond per 1 m	68pF	
Capac. cond/shield per 1 m	130pF	
Cond. resistance per 1 km	53 Ohm	
Shiedl resistance per 1 km	25 Ohm	
Insulation resist. per 1 km	>1G Ohm	
Surge impedence	approx 100 Ohm	