

MCR2022-100

## **BULK BALANCED MICROPHONIC CABLE (100 MT)**

---

Bulk balanced microphonic cable (100 mt) featuring high conductivity. OFC (Oxygen Free Copper) technology, 95% shielding, 2x0,22mm<sup>2</sup> section, 6mm diameter.

MCR2022-100

62c267e6-5ff9-47f0-b0b9-e305d9bd374d.jpg

MCR2022-100

BULK BALANCED MICROPHONIC CABLE (100 MT)

PRODUCT DETAILS

KEY FEATURES

|                                       |
|---------------------------------------|
| Balanced microphonic cable            |
| OFC construction (Oxygen Free Copper) |
| High conductivity                     |
| Mt: 100                               |

SPECIFICATIONS

|                                       |                                   |  |
|---------------------------------------|-----------------------------------|--|
| OFC construction (Oxygen Free Copper) |                                   |  |
| Shielding                             | 95% with spiral copper 80x0,10 mm |  |
| Inner conductors                      | 2x0,22 mm2                        |  |
| Copper strand per conductors          | 28x0,10 mm                        |  |
| Diameter                              | 6 mm                              |  |
| Jacket                                | PVC                               |  |
| Temp. range                           | -20(min)/70 (max)                 |  |
| AWG                                   | 24                                |  |
| Capac. cond/cond per 1 m              | 68pF                              |  |
| Capac. cond/shield per 1 m            | 130pF                             |  |
| Cond. resistance per 1 km             | 53 Ohm                            |  |
| Shiedl resistance per 1 km            | 25 Ohm                            |  |
| Insulation resist. per 1 km           | >1G Ohm                           |  |
| Surge impedence                       | approx 100 Ohm                    |  |