

CHECKLINE-10A

10" BI-AMPED COAXIAL STAGE MONITOR WITH BUILT-IN DSP

CHECKLINE Coaxial Stage Monitor Series is the answer to those rental companies, sound engineers, and bands who need robust, elegant, and handy tools on the stage, but without giving up on high-performance and sonic quality. All three models of the series offer full-range coaxial woofers. The Bi-Amp module delivers 350W (RMS)/ 1000W (Peak) power with absolute sound clarity and reliability. The internal DSP ensures maximum dynamics, overloads and overheating control, and offers 2 EQ factory presets (Full-range, Monitor) and other 5 user-defined, with different equalization curves designed for all main applications. Whether they are used as monitor, full-range speaker, front fill or delayed speaker for indoor/outdoor applications with large dimensions, the CHECKLINE series is the perfect ready-to-use solution for audio professionals.

CHECKLINE-10A

601718b1-7058-4061-a3c8-dfd4b6f61c63.jpg

0778c747-ffd5-493a-a49d-4f71786b6385.jpg

6eb93d89-faa2-463a-a785-a4d4516

CHECKLINE-10A

10" BI-AMPED COAXIAL STAGE MONITOR WITH BUILT-IN DSP

PRODUCT DETAILS

KEY FEATURES

- High-Performance and sonic clarity
- 1.000W (Peak) Class-D bi-amped power module
- 48kHz/24-bit DSP with 2+5 EQ presets, 3-band EQ, Low-Cut, Delay (up to 100m)
- Dual-Band Peak/Overload/Thermal Limiter
- Easy-to-Use DSP Graphic Interface with LCD display and Single Encoder
- Two combo inputs (XLR/6.3 jack with MIC/LINE switches)
- Two boutique-quality microphone preamps
- Rugged, texture-painted plywood enclosure
- Sophisticated coaxial transducers
- 90°x90° sound coverage

SPECIFICATIONS

System Type	Self-powered 10" two-way, coaxial
Frequency Range (-10 dB)	65 Hz - 20 KHz
Frequency Response (±3 dB)	72 Hz - 20 KHz
Coverage Pattern	90° x 90° nominal (HxV)
HF Horn	Coaxial (included)
Crossover Modes	Active / DSP
Crossover Frequency	2.400 Hz

CHECKLINE-10A

10" BI-AMPED COAXIAL STAGE MONITOR WITH BUILT-IN DSP

Power Rating (Continuous/Program)		350W /1.000W
Maximum SPL		126 dB SPL peak
LF Driver		1x10"/1" coaxial transducer
Digital Sound Processor		48kHz/24bit
Input Connectors		2x XLR combo female (Mic/Line)
Input Impedance		9.09kohm (XLR Combo)
Output Connectors		/
Enclosure		15mm, birch plywood
Mounting		35 mm pole socket
Monitor Angle	32°	
Transport	2 integrated handles	
Finish	Black spot painting	
Grille	Powder coated, black, perforated steel with acoustic transparent foam	
Dimensions (WxHxD)	380 x 307.3 x 410 mm	
Net Weight	12,5 kg	
Optional Accessories	CHECKLINE-10 BAG (SKU Code J128J)	