

The Centolight **WideWall Bar** is a compact yet powerful lighting fixture designed to deliver exceptional wall coverage and vibrant effects.

Equipped with 54x3W high-brightness 3-in-1 RGB LEDs and a 10°x60° beam angle, this unit creates stunning washes of color across large surfaces, making it perfect for stages, architectural lighting, event decoration, and outdoor installations. Despite its small size, it packs advanced features, including IR remote control for effortless operation, multiple DMX channel modes (3, 5, 8, or 13), 10 built-in automatic programs, and 55 color presets.

Built with advanced waterproof construction—without reliance on insulating glue this IP65-rated aluminum body ensures reliability and durability even in challenging weather conditions. With variable electronic strobe, dimming curves, color balance adjustment, and smooth color transitions, it offers unmatched versatility. Operate the fixture in DMX, master/slave, or Stand-alone modes, with selectable refresh rates for flicker-free performance in live events and filming scenarios.



Whether you're lighting up a wall for dramatic effects, enhancing an outdoor party, or adding color to an architectural façade, the **WideWall Bar** delivers professional grade performance in a compact package.

























HIGHLIGHTS



UNCOMPROMISING DURABILITY AND RELIABILITY

Built to withstand even the harshest weather conditions, the diecast aluminum body with IP65 protection guarantees long-lasting durability and resistance. The Flicker-free technology and adjustable electronic strobe make it an excellent choice for live events and filming, delivering consistent, uninterrupted performance.

MAXIMUM VERSATILITY AND ADVANCED CONTROL

It provides complete creative freedom with 4 DMX control modes (3, 5, 8, or 13 channels), 10 built-in automatic programs, 55 color presets, and remote control via infrared. Perfect for any type of installation, whether in stand-alone or master/slave mode, ensuring professional performance in every context.







PROFESSIONAL LIGHTING WITH PERFECT GRADIENTS

Thanks to its 54 high-brightness RGB 3-in-1 LEDs and 10°x60° beam angle, the **WideWall Bar** delivers exceptional coverage with smooth and precise color transitions. Ideal for transforming stages, events, or architectural installations with vibrant colors and uniform gradients over large surfaces.



PRODUCT DETAILS

KEY FEATURES

54 x 3W high brightness R/G/B 3in1 LEDs

10°x60° beam angle with silicon lens

3, 5, 8, or 13-channel DMX modes

10 integrated automatic programs and 55 color presets

IR Remote Control

Selectable refresh rate for Flicker-Free operation

Variable electronic strobe, dimming and color changing effect

Stand-alone, Master/Slave and DMX modes

Smart temperature control

IP65

Aluminum die cast body

SPECIFICATIONS

Input Voltage	AC110-240V, 50-60Hz
Power Consumption	150W
LEDs	54x3W, high brightness 3in1 RGB LEDs
Lens	10°x60° silicon
Material	Aluminum
Ambient Temperature	-20°C - 40°C
DMX Channels	3CH / 5CH / 8CH / 13CH
Control Mode	DMX, Master/Slave, Auto, Remote Control





DMX Connectors	Waterproof 3-pin XLR Input/Output
Power Connectors	Waterproof Truecon Input/Output
IP Grade	IP65
Protection Class	1
Fixture Dimensions (WxDxH)	395 x 53 x 85,08 mm(15.5 x 2.1 x 3.35 in.)
Dimensions with handles, barndoor and bracket (WxDxH)	428 x 53 x 192.6 (16.85 x 2.1 x 7.58 in.)
Packing Dimensions (WxDxH)	460 x 143 x 140 mm(18.11 x 5.63 x 5.5 in.)
Product Weight	2.1 kg – 4.6 lbs.
Package Weight	2.7 kg – 5.9 lbs.

