

PASSIVE 2-WAY 2 X 5" COMPACT LOUDSPEAKER WITH COAXIAL TWEETERS AND FIBREGLASS ENCLOSURE – 120 W AES, 16 ?, IP-55 (BLACK)

The Cyclone 55 is an ultra-compact passive loudspeaker designed to deliver high fidelity and definition in both indoor and outdoor environments. With its non-resonant fibreglass construction, IP-55 weather protection, and stylish form factor, it is ideal for coastal and outdoor locations such as beach bars, resorts, cruise ships, and public areas.

Its two-way coaxial transducer configuration provides accurate directivity and phase consistency, while the wide dispersion (110° x 70°) ensures effective coverage with fewer speakers. A dedicated bracket allows for quick, secure mounting and extensive aiming flexibility.















PASSIVE 2-WAY 2 X 5" COMPACT LOUDSPEAKER WITH COAXIAL TWEETERS AND FIBREGLASS ENCLOSURE – 120 W AES, 16 ?, IP-55 (BLACK)

HIGHLIGHTS



IDEAL FOR COASTAL OUTDOOR ENVIRONMENTS

The wide range of adjustments allows the dispersion pattern to be accurately aimed at large audiences, requiring a minimal number of loudspeakers. Well suited to a variety of outdoor and indoor spaces including beach bars, resorts and cruise ships.


MAXIMUM AUDIO PERFORMANCE FROM AN ULTRA-COMPACT IP-55 LOUDSPEAKER

With its coaxial transducer array, fibreglass enclosure, controlled dispersion, and weather-resistant components, the Cyclone 55 delivers clear, wide and natural sound from an aesthetically discreet format. The ideal solution for delivering high-quality audio in challenging outdoor environments.





PASSIVE 2-WAY 2 X 5" COMPACT LOUDSPEAKER WITH COAXIAL TWEETERS AND FIBREGLASS ENCLOSURE – 120 W AES, 16 ?, IP-55 (BLACK)



COMPACT, NON-RESONANT FIBREGLASS ENCLOSURE

Lightweight yet robust construction, minimizing unwanted resonances even at high SPL thanks to its material and structure.

CUSTOM COLORS AVAILABLE UPON REQUEST

In addition to the 3 iconic Void brand colors -red, white and black- Cyclone 55 can be produced in several other custom colors (the colors visible in the image are examples for illustrative purposes)





PASSIVE 2-WAY 2 X 5" COMPACT LOUDSPEAKER WITH COAXIAL TWEETERS AND FIBREGLASS ENCLOSURE – 120 W AES, 16 ?, IP-55 (BLACK)

PRODUCT DETAILS

KEY FEATURES

Two 5" woofers in a reflex-loaded cabinet with coaxially mounted soft dome tweeters for coherent and low-distortion sound reproduction.

Wide dispersion and efficient coverage: controlled directivity of 110° horizontal × 70° vertical, enabling wide audience coverage with fewer loudspeakers.

IP-55 weather protection: UV-resistant coating and marine-grade stainless steel fittings ensure reliable performance in outdoor or marine environments.

Secure and adjustable mounting: supplied wall bracket allows for secure, flexible installation with broad aiming capability.

SPECIFICATIONS

Frequency Response	70 Hz - 23 kHz ±3 dB
Efficiency	92 dB 1W/1m
Crossover Points	3.6 kHz passive
Nominal Impedance	16 ?
Power Handling	120 W AES
Maximum Output	112 dB cont, 118 dB peak
Driver Configuration	2x 5" LF, 2X 1" soft dome HF tweeter
Dispersion	110°H x 70°V
Connectors	Phoenix Connectors with link out
Dimensions (W x H x D)	309mm x 192mm x 232mm
Weight	3.2 kg (7.1 lbs)





PASSIVE 2-WAY 2 X 5" COMPACT LOUDSPEAKER WITH COAXIAL TWEETERS AND FIBREGLASS ENCLOSURE – 120 W AES, 16 ?, IP-55 (BLACK)

Enclosure	Fibreglass composite
Rigging	Wall bracket included, Type 51 plate
Finish	Smooth cellulose
Colors	Black (Custom colours available upon request)

