


IT2808

1X12" SUBWOOFER, 600 W AES, 8 Ω, REFLEX, WITH FIBERGLASS CABINET (BLACK)

The Cyclone Bass brings a new level of aesthetics and performance to high-visibility outdoor environments. Equipped with a high-powered 12" transducer, this passive subwoofer delivers effective low-frequency extension, with a response from 40 to 160 Hz and peak SPL of 130 dB. Its fibreglass construction with smooth cellulose finish is designed for long-term use in demanding conditions, supported by its IP-55 rating for protection against moisture, rain, and corrosive atmospheres.

The design features Phoenix connectors with link-out, making wiring and daisy-chaining installations straightforward. The driver operates in a direct-radiating reflex configuration, with a 4" copper voice coil wound on a high-quality former for reliable thermal and power handling. The enclosure includes integrated threaded inserts for wall or ceiling mounting and is available in any custom RAL colour, making the Cyclone Bass a perfect choice for outdoor bars, clubs, hotels, and restaurants.



IT2808

1X12" SUBWOOFER, 600 W AES, 8 Ω, REFLEX, WITH FIBERGLASS CABINET (BLACK)

HIGHLIGHTS



SUPERIOR OUTDOOR POWER AND DURABILITY

The Cyclone Bass is a 12" passive subwoofer with **600 W AES power handling** and a **130 dB peak SPL**, capable of delivering deep, precise bass in challenging outdoor environments. The **moulded fibreglass enclosure** offers excellent **weather resistance with an IP-55 rating**, while the **UV-resistant paint finish** and marine-grade stainless steel fittings ensure long-term reliability even in corrosive conditions. Ideal for beach bars, theme parks, and high-profile outdoor venues.

ELEGANT DESIGN AND EASY INSTALLATION FOR PROFESSIONAL SETTINGS

The Cyclone Bass combines refined aesthetics, available in a wide range of customizable colours, with technical solutions such as **Phoenix connectors with link out** for secure and quick wiring. The compact trapezoidal cabinet with integrated threaded inserts allows flexible wall or ceiling mounting, fitting perfectly in clubs, hotels, and lounges. Attention to construction details, like the 4" voice coil on an aluminium frame and treated paper cone, guarantees uncompromised power and reliability.



IT2808

1X12" SUBWOOFER, 600 W AES, 8 Ω, REFLEX, WITH FIBERGLASS CABINET (BLACK)



CUSTOM COLORS AVAILABLE UPON REQUEST

In addition to the 3 iconic Void brand colors -red, white and black- Cyclone Bass can be produced in several other custom colors (the colors visible in the image are examples for illustrative purposes)

IT2808

1X12” SUBWOOFER, 600 W AES, 8 Ω, REFLEX, WITH FIBERGLASS CABINET (BLACK)

PRODUCT DETAILS

KEY FEATURES

- Reflex-loaded subwoofer with high-power 12” transducer, for deep and efficient low-frequency output
- Compact fibreglass cabinet with smooth finish, designed to resist vibration and moisture
- UV resilient paint
- Phoenix connectors with loop-out, for fast and secure wiring in multi-speaker installations
- Marine-grade stainless steel fittings and 75 plate mounting, for robust and durable installations

SPECIFICATIONS

Frequency Response	40Hz - 160Hz -3dB
Efficiency	97dB 1w/1m
Crossover Point	80Hz-160Hz Active
Impedance	8 ohms
Power Handling	600 Watts RMS
Maximum Output	124dB cont, 130dB peak
Driver Configuration	1 x 12"
Connectors	Phoenix Connectors with link out
Dimensions (W x H x D)	490mm x 378mm x 479mm
Weight	33.5kg (73.8lbs)
Enclosure	Fibreglass
Finish	Smooth cellulose

IT2808

1X12" SUBWOOFER, 600 W AES, 8 Ω, REFLEX, WITH FIBERGLASS CABINET (BLACK)

Mounting	Type 75 plate
IP Rating	IP-55 (BS EN 60529:1992 +A2:2013)
Colors	Black