

The Indigo 6 Pro is a high-performance evolution of the popular Indigo 6s: a compact two-way loudspeaker delivering high efficiency, sonic clarity and flexible mounting options. Its true point-source radiation and 90° x 90° controlled dispersion make it perfect for near-field applications or environments requiring precise intelligibility and detail.

Its sculpted fibreglass enclosure with smooth gloss or matte finish makes it ideal for visually-led environments. When combined with an Indigo Sub, it becomes suitable for mediumsized bars and lounges, or for fill duties in larger club spaces already featuring a main dance floor system.









### **HIGHLIGHTS**



## MODERN AND ELEGANT DESIGN IN FIBERGLASS WITH GLOSSY OR MATTE FINISH

The cabinet is made from rugged fibreglass-reinforced plastic, with a sculpted form factor that enhances the aesthetics of modern and style-conscious spaces. Available in both smooth gloss (cellulose) and fine-textured matte finishes, it suits a variety of architectural and decorative needs. The ultra-modern look, combined with material durability, makes the Indigo 6 Pro ideal for visually demanding installations such as high-end lounges, restaurants, and retail environments.

## 6.5" WOOFER WITH 1" COAXIAL COMPRESSION DRIVER FOR HIGH FREQUENCIES

The Indigo 6 Pro features a coaxial transducer with a reflex-loaded 6.5" woofer and a 1" neodymium compression driver mounted coaxially, radiating through a precision-machined waveguide. This true point-source configuration ensures high efficiency, coherent response, and a wide 90° x 90° symmetrical dispersion, reducing unwanted reflections and enhancing intelligibility even in acoustically challenging environments.







### CUSTOM COLORS AVAILABLE UPON REQUEST

In addition to the 3 iconic Void brand colors -red, white and black- Indigo 6 PRO can be produced in several other custom colors (the colors visible in the image are examples for illustrative purposes)



### **PRODUCT DETAILS**

#### **KEY FEATURES**

Ultra-modern appearance for style-led environments

Wide conical 90°H x 90°V dispersion pattern

Sculpted fibreglass enclosure

Wall bracket (included), subwoofer mounting bracket (optional)

### **SPECIFICATIONS**

Fraguency Bosponso	68 Hz - 21 kHz ±3 dB
Frequency Response	00 HZ - Z1 KHZ ±3 UD
Efficiency	93 dB 1W/1m
Crossover Points	2.2 kHz passive
Nominal Impedance	8 ?
Power Handling	200 W AES
Maximum Output	116 dB cont, 122 dB peak
Driver Configuration	1x 6.5" LF, 1x 1" coaxial high frequency compression driver
Dispersion	90°H x 90°V
Protection	HF electronic device
Connectors	Phoenix connector
Weight	5.2 kg (11.5 lbs)
Enclosure	Fibreglass
Rigging	i6 wall bracket (supplied), i12 bracket to mount Indigo 6s above Indigo 12 (optional)





Finish Smooth cellulose or fine textured matt

Grille Perforated steel with foam filter

Dimensions (W x H x D) 273mm x 209mm x 163mm

**Colors** White (custom colors available upon request)

