

VENU 112v2

## 12" COMPACT REFLEX SUBWOOFER, 8 ?, 600 W (BLACK)

The Venu 112 V2 is a compact 12" subwoofer designed to deliver tight and powerful bass in a discreet, easy-to-integrate format. Its high-excursion transducer with a 4" voice coil ensures precise and deep low-frequency reproduction, reaching down to 40 Hz and delivering a maximum peak SPL of 132 dB. The recessed rear connector panel allows for flush wall placement, while the dual speakON™ and Phoenix connectors ensure fast and reliable setup. The enclosure, built from 15 mm multi-laminate birch plywood, features mounting points and an integrated M20 top hat, making the Venu 112 V2 suitable for both fixed installations and touring use.



VENU 112v2

# 12" COMPACT REFLEX SUBWOOFER, 8Ω, 600 W (BLACK)

---

## HIGHLIGHTS

---



### COMPACT POWER WITH PRECISION

The **12"** high-excursion driver with **4"** copper voice coil delivers tight response and excellent thermal durability, ensuring **defined low-end even at high SPL levels**.

### REFLEX SYSTEM DESIGN FOR DEEPER BASS

The **compact reflex design** provides **extended reproduction down to 40 Hz**, making the Venu 112 V2 ideal for **spaces needing powerful bass without bulky enclosures**.



VENU 112v2

**12" COMPACT REFLEX SUBWOOFER, 8 ?, 600 W  
(BLACK)****CUSTOM COLORS AVAILABLE UPON  
REQUEST**

The Venu 112 V2 is ingeniously enhanced in aesthetics as well as functionality thanks to its colour customisation providing the chance to own a bespoke product that will compliment any location (the colors visible in the image are examples for illustrative purposes)

VENU 112v2

# 12" COMPACT REFLEX SUBWOOFER, 8 ?, 600 W (BLACK)

## PRODUCT DETAILS

### KEY FEATURES

Recessed connector panel allows flush wall placement while maintaining full accessibility and durability

Fast and secure connectivity with dual speakON™ and Phoenix connectors featuring link outs for quick daisy-chaining

Durable 15 mm birch plywood construction, engineered to be resonance-free and long-lasting for permanent installs

Fine-textured polyurethane coating, highly resistant to scratches and impact, ideal for public or commercial spaces

Integrated rigging points for wall or ceiling brackets, plus M20 top hat included for mobile or pole-mounted setups

### SPECIFICATIONS

<b>Frequency Response</b>	40 Hz - 160 Hz ±3 dB
<b>Efficiency</b>	99 dB 1W/1m
<b>Crossover points</b>	80 Hz - 160 Hz active
<b>Nominal impedance</b>	8 ?
<b>Power Handling</b>	600 W AES
<b>Maximum output</b>	126 dB cont, 132 dB peak
<b>Driver configuration</b>	1x 12" LF
<b>Connectors</b>	1x Phoenix with link out and 1x speakON™ with link out
<b>Weight</b>	27 kg (59.5 lbs)
<b>Dimensions (W x H x D)</b>	490mm x 378mm x 430mm
<b>Enclosure</b>	15 mm birch plywood
<b>Mounting</b>	Optional top hat Yoke bracket positions Type 75 plate

VENU 112v2

**12" COMPACT REFLEX SUBWOOFER, 8 ?, 600 W  
(BLACK)**

<b>Finish</b>	Textured polyurethane
<b>Grille</b>	Perforated steel with foam filter
<b>Colors</b>	Black (custom color available upon requests)