GS 230B

7M STRUCTURAL TOWER 30X30 BLACK, MAX LOAD 750KG (F70TBT112)

Our **GS 230** Ground Support structural tower has been designed for lifting loads up to 750 kg at a maximum working height of 7 m (extendable up to 8 m). Made of aluminium and steel, it can be used with an ER30, EC30 or EC40 truss bolted directly to the trolley and lifted with a self-braking winch fitted with a crank (optional motor). Designed and manufactured for indoor and outdoor use. Available in Silver and Black. Connection set no included.

GS 230B

96b215c3-634b-4b45-b051-bef2e9885fa1.png

105ff8a4-b282-4faf-9c8f-f4166221c4e3.png

5479661e-e893-4760-909f-e763c6c

cef5b43e-5c98-414f-9ea0-653965baaa69.png

b88efa13-5243-411d-ba8f-308bd78f2702.png

95388363-beb6-4cf6-9df9-62a359

bec7d4a4-fb53-4de2-b553-f9aae2eefd79.png

0c1b37ec-401c-4659-9f56-a68335d0d67a.png

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

GS 230B

7M STRUCTURAL TOWER 30X30 BLACK, MAX LOAD 750KG (F70TBT112)

PRODUCT DETAILS

KEY FEATURES

- EC30 L truss mast
- Compatible with ER30, EC30 and EC40 trusses
- Safety system with locking sling. Easy assembly

SPECIFICATIONS

Material	Aluminum and steel
Maximum height	7 m / 22,96 ft
No. of sections	5 sections
Maximum Load	750 kg / 1653,47 lbs
Elevation system	Manual drive (winch) as standard, motor as option
Cable diameter	6 mm / 0,28 in
Unfolded base	2,84 x 2,84 m / 9.32 x 9.32 ft
Folded Base	0,72 x 0,64 m / 2.36 x 2,09 ft
Security systems	Yes
Weight	85 Kg / 187,39 lbs
Aluminum thickness	2 mm / 0,078 in
Main tube diameter	50 mm / 1,96 in
Down tube diameter	16 mm / 0,63 in
Colour	Black

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

GS 230B

7M STRUCTURAL TOWER 30X30 BLACK, MAX LOAD 750KG (F70TBT112)

Section dimensions	30 x 30 cm / 11,81 x 11,81 in
Winch	ALKO 1201 PLUS

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it