

GS140-900B

9M BLACK STRUCTURAL TOWER 40X40 2000 KG (F70TGS149)

Ground support truss tower with mast truss EC40 PROGS. The mast sections have one side ladder braces disposition to facilitate safe and easy access to top truss by fulfilling the necessary preventive measures. The tower can be used with the Heavy Duty series and EC40 with the needed adaptator. The GS140 sleeve block is a fully bolted structural element that offers much more precision and resistance than conventional welded units. Silver and black colour available.







sample photo



GS140-900B

9M BLACK STRUCTURAL TOWER 40X40 2000 KG (F70TGS149)



GS140-900B

9M BLACK STRUCTURAL TOWER 40X40 2000 KG (F70TGS149)

PRODUCT DETAILS

KEY FEATURES

Truss mast EC40 PROGS

High load series

Easy assembly

Available in 9 and 12 meters

SPECIFICATIONS

Material	Aluminum and steel	
Maximum height	9m / 29,6 ft	
No. of sections	4: 1xEC4005PROGS+1xEC402PROGS+2xEC403PROGS	
Maximum Load	2000 kg / 4409,25 lbs	
Elevation system	Engine	
Unfolded base	4,35 x 4,35 m / 14,27 x 14,27 ft (with legs)	
Folded Base	79 x 79 cm / 2,62 x 2,62 ft (without legs)	
Weight	253 kg / 558 lbs	
Aluminum thickness	4 mm / 0,16 in	
Main tube diameter	50 mm / 1,97 in	
Down tube diameter	25 mm / 0,98 in	
Color	Black	
Section dimensions	39 x 39 cm / 15,74 x 15,74 in	

GS140-900B

9M BLACK STRUCTURAL TOWER 40X40 2000 KG (F70TGS149)

Compatible accessories

T140-SM / T140-SMPA

Compatible truss

EC52, EC76, EC40PROGS