

GS 130 700

## STRUCTURAL TOWER 30\*30 OF 7M HEIGHT, MAX LOAD 750KG (T110)

---

Structural tower with EC30 L truss mast for a maximum working height of 7m and with a capacity of 750 Kg in manual lifting version. To anchor the truss to the tower it is necessary to acquire the accessory ATR-308 or ATR-30845, depending on the truss to be used. Supplied for a height of 7 meters, possibility of adding 1 additional truss section for a maximum height of 8 meters. Silver or Black is available.

GS 130 700

2ebbf1de-78cf-4a04-8f25-bd0b82681f6e.png

ac8ad894-4b61-4bee-a555-6af786cdd91b.png

5fc8ad4b-1a83-4c31-82df-1fc74d9

43d8dc7d-ff74-4005-9c2a-bfdb285b4136.png

GS 130 700

# STRUCTURAL TOWER 30\*30 OF 7M HEIGHT, MAX LOAD 750KG (T110)

## PRODUCT DETAILS

### KEY FEATURES

EC30 L truss mast

Safety system with locking sling

Easy assembly

### SPECIFICATIONS

|                           |                                |
|---------------------------|--------------------------------|
| Material                  | Aluminum and steel             |
| Maximum height            | 8 m / 22,96 ft                 |
| Folded Height             | 1,35 m / 4,43 ft               |
| No. of sections           | 5                              |
| Maximum Load              | 750 kg / 1653,47 lbs           |
| Max load (mechanism mode) | 1200 kg / 2645,55 lbs          |
| Elevation system          | Manual drive (Winch)           |
| Cable diameter            | 7 mm / 0,28 in                 |
| Unfolded base             | 2,1 x 2,1 m / 6,89 x 6,89 ft   |
| Folded Base               | 1,05 x 0,63 m / 3,44 x 2,07 ft |
| Security systems          | T110ESB                        |
| Weight                    | 7 m                            |
| Aluminum thickness        | 2 mm / 0,078 in                |
| Main tube diameter        | 50 mm / 1,96 in                |

GS 130 700

## STRUCTURAL TOWER 30\*30 OF 7M HEIGHT, MAX LOAD 750KG (T110)

---

|                        |                                             |
|------------------------|---------------------------------------------|
| Down tube diameter     | 16 mm/ 0,63 in                              |
| Colour                 | Silver                                      |
| Section dimensions     | 30 x 30 cm / 11,81 x 11,81 in               |
| Compatible accessories | T110-SPM / T110-SPMPA / ATR-308 / ATR-30845 |
| Winch                  | ALKO 1201 PLUS                              |