

GS140-1200

12M STRUCTURAL TOWER 40X40 2000 KG (T14012)

Ground support truss tower with mast truss EC40 PROGS. The mast sections have one side ladder braces disposition to facilitate safe and easy access to top truss by fulfilling the necessary preventive measures. The tower can be used with the Heavy Duty series and EC40 with the needed adaptator. The GS140 sleeve block is a fully bolted structural element that offers much more precision and resistance than conventional welded units. Silver and black colour available.

GS140-1200

myN3dZQe5SoqSUN1760098866_Screenshot 2025-10-01 175527.png

3qQdNQaLhxf79bb1760098871_Screenshot 2025-10-01 1755

NeoiO4dxc1CD9Bq1760098896_Screenshot 2025-10-01 175658.png

LCOJ0vuGLu4dcgF1760098901_Screenshot 2025-10-01 17571

AhE02AhhHALvhDR1760098918_Screenshot 2025-10-01 175821.png

6XfXVWq7jEpjnqd1760098927_Screenshot 2025-10-01 175841

GS140-1200

12M STRUCTURAL TOWER 40X40 2000 KG (T14012)

PRODUCT DETAILS

KEY FEATURES

Truss mast EC40 PROGS

High load series

Easy assembly

Available in 9 and 12 meters

SPECIFICATIONS

Material	Aluminum and steel	
Maximum height	12m / 39,4 ft	
No. of sections	5: 1xEC4005PROGS+1xEC402PROGS+3xEC403PROGS	
Maximum Load	2000 kg / 4409,25 lbs	
Elevation system	Engine	
Unfolded base	4,35 x 4,35 m / 14,27 x 14,27 ft (with legs)	
Folded Base	79 x 79 cm / 2,62 x 2,62 ft (without legs)	
Weight	280 kg / 617 lbs	
Aluminum thickness	4 mm / 0,16 in	
Main tube diameter	50 mm / 1,97 in	
Down tube diameter	25 mm / 0,98 in	
Color	Silver	
Section dimensions	39 x 39 cm / 15,74 x 15,74 in	

GS140-1200

12M STRUCTURAL TOWER 40X40 2000 KG (T14012)

Compatible accessories

T140-SM / T140-SMPA

Compatible truss

EC52, EC76, EC40PROGS