

Positioned as the ideal mid-point solution between the Cyclone 55 and Cyclone 10 models, the Cyclone 8 delivers an installation-friendly, compact and rugged package with an IP-55 rating, making it perfectly suited for both indoor and outdoor use. Whether used as a standalone solution in beach bars, lounges, restaurants, cruise ships or hotels, or as area fill within a larger club system, the Cyclone 8 always provides high-quality sound.

Its advanced port design minimizes air turbulence while maximizing low-frequency performance, and the combination of a coaxially mounted 8" low-frequency transducer with a 1" high-frequency compression driver ensures high efficiency and clarity, despite the unit's compact size. The fibreglass composite enclosure, paired with UV-resistant paint and marine-grade stainless steel fittings, guarantees long-lasting durability even in harsh environments. Flexible mounting options allow for quick and secure installation, with a wide range of adjustment for optimal coverage.













### **HIGHLIGHTS**



### HIGH-PERFORMANCE WEATHERPROOF DESIGN IN A COMPACT FORM

By combining premium components, a fibreglass enclosure, and an IP-55 protection rating, the Cyclone 8 delivers professional-grade audio performance in challenging outdoor environments—without compromising on aesthetics or ease of installation. It offers a smart balance of acoustic efficiency, rugged build, and versatile design, making it ideal for hospitality, retail, and public venues.

### ANTI-RESONANCE STRUCTURE FOR GREATER CLARITY

Due to its structure and construction (with fiberglass cabinet), Cyclone 8 allows for a clear and reliable response while consistently reducing resonances.





# 8" PASSIVE 2-WAY SURFACE MOUNT LOUDSPEAKER IN FIBREGLASS (WHITE)



### CUSTOM COLORS AVAILABLE UPON REQUEST

In addition to the 3 iconic Void brand colors -red, white and black- Cyclone 8 can be produced in several other custom colors (the colors visible in the image are examples for illustrative purposes)



### **PRODUCT DETAILS**

#### **KEY FEATURES**

Two-way passive loudspeaker with 8" and 1" coaxial driver, for coherent and high-efficiency reproduction

UV-resistant paint and marine-grade stainless steel fittings, for long-term durability in harsh conditions

Adjustable 80 plate mounting system, for fast and directional installation

IP-55 weather protection, suitable for permanent outdoor use in coastal or urban environments

#### **SPECIFICATIONS**

Frequency Response	70 Hz - 20 kHz ±3 dB
Efficiency	94 dB 1W/1m
Crossover Points	2 kHz passive
Nominal Impedance	8?
Power Handling	200 W AES
Maximum Output	118 dB cont, 121 dB peak
Driver Configuration	1 x 8", 1 x 1" coaxial
Dispersion	90°H x 90°V
Connectors	Phoenix
Weight	14 kg (31 lbs)
Dimensions (W x H x D)	450mm x 281mm x 293mm
Enclosure	Fibreglass composite
Mounting	Type 80 plate





Colors White (Custom colours available upon request)

IP rating IP-55 (BS EN 60529:1992 +A2:2013)

