

TK 5010

TOP-LOAD LIFTER 4,9M 100KG BLACK (T102D)

The lifting tower TK 5010 is designed to lift vertical loads up to 100 Kg and 4,9 m. Comprised of 3 extensible steel profiles lifted by a high strength steel cable. Safety mechanism based on steel pins that lock the tower into the desired height automatically. Legs equipped with non-slip rubber plates. The entire system is operated with a manual winch. T 102 is a very versatile lifting tower suitable for small events.

TK 5010

6a7a0d38-ba0e-495d-8017-160a0f244897.png

0509f808-f3f2-4d87-aadb-b16913a1259d.png

1a91c0f1-a42a-4b7c-966e-8a90e

773b3143-d441-4789-b6a4-60bd4ef6e29e.png

ab0c671c-6c17-495a-8ec8-b151c8242de2.png

TK 5010

TOP-LOAD LIFTER 4,9M 100KG BLACK (T102D)

PRODUCT DETAILS

KEY FEATURES

Great versatility

Wire Drive

Levelable leg system

SPECIFICATIONS

Material	Steel
Folded Height	2,1 m/ 6,89 ft
Extended base dimensions	2,1 x 2,1 m/ 6,89 x 6,89 ft
Folded base dimensions	0,36 x 0,36 m / 1,18 x 1,18 ft
Maximum height	4,9 m / 16,4 ft
Minimum height	2,1 m/ 6,89 ft
Minimum Load	25 Kg/ 55,12 lbs
Max load (mechanism mode)	100 Kg / 220,46 lbs
Winch	350 Kg / 771,62 lbs
Cable diameter	4 mm / 0,16 in
Noise Emission	70 dB
Compatible accessories	ATCMOS / ATCMOB / ATCLTS / ATC6FS / ATC29S / ATCBAS
Security systems	Self locking safety pins
Standards and Certifications	CE, DGUV, BGV C1, BGG 912
Weight	35 Kg / 77,16 lbs
Unfolded base diameter	2,01 m / 6,59 ft