

TK 5322

TOP-LOAD LIFTER 5,3M 225KG BLACK (T105D)

The lifting tower T 105 is designed to lift vertical loads up to 225 Kg and 5,3 m. Comprised of 4 extensible steel profiles lifted by a high strength steel cable. Safety mechanism based on steel pins that lock the tower into the desired height automatically. Legs equipped with non-slip rubber plates. The entire system is operated with a manual winch.

TK 5322

43ba7d76-5035-4107-9ac4-bdb4749f3fb2.png

b2f8dda7-5d8d-41c3-9a90-d5e9759799fb.png

2f1bd723-b820-4a50-abc4-9d94b

5a09eef9-d2cb-49ed-9bb2-c40a7aa00a77.png

02276a64-ac18-41a2-8818-76f04e2744d6.png

TK 5322

TOP-LOAD LIFTER 5,3M 225KG BLACK (T105D)

PRODUCT DETAILS

KEY FEATURES

Wire Drive

Levelable leg system

High load capacity

SPECIFICATIONS

Material	Steel
Folded Height	1,8 m/ 5,91 ft
Extended base dimensions	2,15 x 2,15 m / 7,05 x 7,05 ft
Folded base dimensions	0,46 x 0,46 m / 1,51 x 1,51 ft
Maximum height	5,3 m/ 17,39 ft
Minimun height	1,8 m / 5,91 ft
No. of sections	4
Minimum Load	25 Kg / 55,12 lbs
Max load (mechanism mode)	225 Kg/ 496,04 lbs
Winch	900 Kg / 1984,16 lbs
Cable diameter	7 mm / 0,28 in
Noise Emission	75 dB
Compatible accessories	ATCMOS / ATCMOB / ATCLTS / ATC6FS / ATC29S / ATCBAS
Security systems	Self locking safety pins
Standards and Certifications	CE, DGUV, BGV C1, BGG 912
Weight	88 Kg / 194 lbs

TK 5322

TOP-LOAD LIFTER 5,3M 225KG BLACK (T105D)

Unfolded base diameter

2,2 m / 7,22 ft