

GF22A

ULTRA-COMPACT 2X2" FULL-RANGE ACTIVE SPEAKER (BLACK)

GF22A

GF22A is an ultra-compact active loudspeaker with 2 2" drivers and built-in amplifier, designed to deliver high-level sound performance by ensuring full-bodied bass frequencies compared to other speakers of the same size thanks to the bass reflex design and optimized transducer filtering that ensure superior sound quality in an extremely discreet format.

The minimalist design integrates easily with any architectural style, while the IP54-rated ABS cabinet ensures reliability and durability even in challenging environmental conditions.

The GF22A's real strength lies in its built-in Class D amplifier, which delivers 100W of power at 2? while keeping power consumption to a minimum (30W at 1/8 rated load). Thermal and overload protections ensure maximum operational stability, making it perfect for professional installations where compactness and safety are critical.

With wide coverage (90° V | 90° H) and a frequency response up to 20 kHz, GF22A is ideal for crystal-clear voice and music reproduction. For deeper musical performance, pairing with the GS6 subwoofer is recommended.


98e64364-449d-4e9b-9257-d32928098a84.png

Class-D

GF22A

ULTRA-COMPACT 2X2" FULL-RANGE ACTIVE SPEAKER (BLACK)

HIGHLIGHTS




SUPERIOR AUDIO PERFORMANCE IN A COMPACT FORMAT

The **GF22A** manages to combine extreme compactness and sound quality, particularly in the low frequency response, thanks to the **bass reflex design and optimised filtering** which allow it to **exceed the typical expectations of a 2" speaker**, making it a unique proposition for applications where **small size and sound quality are both essential**.

ULTRA-COMPACT FORMAT AND IP54 RATING FOR DISCREET INDOOR/OUTDOOR INSTALLATIONS

Just 60 mm wide, with dust and splash protection—perfect for elegant applications in both public and private venues.



GF22A

ULTRA-COMPACT 2X2" FULL-RANGE ACTIVE SPEAKER (BLACK)

PRODUCT DETAILS

KEY FEATURES

Ultra-compact (2x2") line array design: The small format allows for discreet installations in environments where space is limited or where minimal aesthetics are required, without sacrificing sound quality.

Wide 90° both vertical and horizontal coverage: allows you to reach large listening areas with a reduced number of speakers, maintaining clarity and intelligibility.

Durable ABS cabinet with IP54 rating: guarantees protection from dust and splashes, making the speaker suitable for both indoor and outdoor installations in permanent contexts.

Integrated digital amplifier (Class D): delivers 100W of power into 2? with low consumption and maximum efficiency, ideal for low voltage powered systems (12–24 V DC).

SPECIFICATIONS

Type	Active loudspeaker
Transducers	2x2" ferrite magnet woofer
Frequency Response	90 Hz - 20 kHz (-6dB)
Max SPL	103 dB
Coverage	V. 90° H. 90°
Operating Range	12-24 V DC
Mains Connector	2x Phoenix connector (4-pin euroblock) Balanced Line in Mute contact Power out
Impedance	16 ?
Amp Module	1-channel Class-D audio amplifier
Output Power	100W @ 2? (24V power)
Power Consumption	30W Rated Load 1/8 Max Power

GF22A

ULTRA-COMPACT 2X2" FULL-RANGE ACTIVE SPEAKER (BLACK)

Protections	Thermal Protections (Power limiting - Thermal Shutdown), Short- circuit/overload output protections	
Dimensions (W x H x D)	60 x 590 x 72 mm (2,36 x 23,23 x 2,83 in)	
Weight	1,3 kg (2,87 lbs)	
Material	ABS	
Colors	Black	
IP Rating	IP54	