

XPRS-1182ST

18" REFLEX LOADED ACTIVE SUBWOOFER

Versatile XPRSion

XPRS-1182ST

The XPRS2 Series couples the versatility and mobility of the original XPRS Series with elevated sound-performance and audio intelligibility to deliver a high-caliber speaker system for mobile DJs, live sound, houses of worship, rental and fixed installations.

b3668113-9774-424c-912c-a60686017bb1.jpg

0966c050-5705-49bb-9884-7030d57bc476.png

57fedf3a-c846-454d-bf84-841de

cf8bf7c5-30da-4437-8340-d23917e5b5bb.jpg

e5147b71-c43b-4f46-9b91-2161cc3a6fda.jpg

XPRS-1182ST

18" REFLEX LOADED ACTIVE SUBWOOFER

PRODUCT DETAILS

KEY FEATURES

Powerful Class D Amplification

High Quality, Robust Build

Three DSP Modes

Accurate Audio Performance / Frequency Response

SPECIFICATIONS

Type	18 inch active subwoofer
Amplifier Output	Class D 4000W peak
Supported voltages	110 V to 240 V (50 Hz/60 Hz)
Power consumption	800 W
Frequency Range	40 – 120 Hz
DSP modes	EQ Mode Select - 3 DSP Preset Modes(Switch), LPF, POLARITY
DSP presets modes	BOOST, EXTENDED LF, NORMAL
Maximum Sound Pressure	130 dB
Inputs	Left Mono (Combo), Right (Combo)
Outputs	Left Mono (XLR), Right (XLR)
Driver	18" ferrite LF cone driver
Finish	Black paint, Rubber feet
Handle	2 metal handles (on left side and top)
Pole socket	M20 socket
Enclosure	Plywood (TSCA)

XPRS-1182ST

18" REFLEX LOADED ACTIVE SUBWOOFER

Amplifier Protection	Thermal limiting, Digital compressor
Driver Protection	Short circuit protection
Power unit Protection	Primary AC mains overcurrent protection, Primary AC mains overvoltage protection
Dimensions (WxHxD)	661x535x536,5 mm
Weight	32.3 kgs
What's in the box	XPRS1182ST x 1 (not sold as a pair), Powerd cord, Quick start guide, Important Safety Precautions